



Uni Install outdoor excl. light source

Technical data

Hole diameter:	Ø75 mm
Height:	63 mm
Front size:	Ø87 mm
Voltage:	220-240VAC 50 Hz
Socket:	GU10
Light source:	Max. 7.5W LED
Tilt angle:	30°
IP-class:	IP44 (depends on the light source)
Insulation class:	Class II
Material:	Plastic, acid resistant stainless steel AISI 316
Possibility of through wiring:	Yes (3G1.5)



*The drawing is not drawn to scale

Product information

- Approved for installation directly in the insulation and flammable materials
- Low mounting depth
- Quick and easy mounting
- Mounting with screws or adjustable springs
- Screwless terminal block in the connector box
- Possibility of mounting with cable or 16 mm flex tub
- Adjustable springs for ceiling thickness up to 44 mm
- Adjustable screws for ceiling thickness up to 35 mm
- Designed and developed in Denmark

This luminaire is compatible with bulbs of the energy classes:

A++

A+

A

B

C

D

E

Downlight

874/2012

NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.

Item no.	EAN no.	Colour	Front design
1293	5704629012936	White	Round
1294	5704629012943	Brushed steel	Round
1299	5704629012998	Black	Round