SIEMENS

Product data sheet 5SY6206-7



CIRCUIT BREAKER 400V 6KA, 2-POLE, C, 6A, D=70MM

Similar to image

Technical data:			
Overvoltage class		3	
type of voltage		AC/DC	
Tripping characteristic class		С	
Degree of pollution		3	
Mounting depth	mm	70	
Energy limiting class		3	
Number of poles		2	
Number of pitch units for width		2	
Product function / n-switching		No	
Supply voltage frequency / rated value	Hz	50	
Switching capacity current / in accordance with IEC 60947-2 / rated value	kA	30	
Breaking capacity current / acc. to EN 60898 / rated value	kA	6	
Supply voltage / for AC / rated value	V	400	
Current / for AC / rated value	А	6	
Protection class IP		IP20, with connected conductors	
Product extension / can be installed / supplementary device		Yes	
power loss		-	

Operational voltage Um - rated current In - Rated make-break capacity Icn - Rated service short-circuit breaking capacity Ics - Rated ultimate short-circuit breaking capacity Icu - Tripping characteristics Number - Tripping characteristic/-class Conventional tripping current I2, (x ln) - rated current In IEC, DIN/VDE - rated current In / IEC, DIN/VDE - • at 30 Cel A 6 • at 40 Cel A 5.64 • at 45 Cel A 5.418 • at 50 Cel A 5.19 • at 55 Cel A 4.968 • at 60 Cel A 1.50m/s² at 11ms half-sine			
Rated make-break capacity Icn Rated service short-circuit breaking capacity Ics Rated ultimate short-circuit breaking capacity Icu Tripping characteristics Number Tripping characteristic/-class Conventional tripping current I2, (x In) rated current In IEC, DIN/VDE Tripping characteristic/-class Test current I4, hold (x In) rated current In / IEC, DIN/VDE • at 30 Cel • at 40 Cel • at 45 Cel • at 55 Cel • at 55 Cel • at 66 Cel A 4.968 A 4.74	Operational voltage Um		-
Rated service short-circuit breaking capacity Ics Rated ultimate short-circuit breaking capacity Icu Tripping characteristics Number Tripping characteristic/-class Conventional tripping current I2, (x In) rated current In IEC, DIN/VDE Tripping characteristic/-class Test current I4, hold (x In) rated current In / IEC, DIN/VDE • at 30 Cel • at 40 Cel • at 45 Cel • at 50 Cel • at 55 Cel • at 55 Cel • at 60 Cel • at 60 Cel	rated current In		-
Rated ultimate short-circuit breaking capacity lcu Tripping characteristics Number Tripping characteristic/-class Conventional tripping current I2, (x ln) rated current ln IEC, DIN/VDE Tripping characteristic/-class Test current I4, hold (x ln) rated current ln / IEC, DIN/VDE • at 30 Cel • at 40 Cel • at 45 Cel • at 45 Cel • at 50 Cel • at 50 Cel • at 50 Cel • at 60 Cel • at 60 Cel	Rated make-break capacity Icn		-
Tripping characteristics Number Tripping characteristic/-class Conventional tripping current I2, (x In) rated current In IEC, DIN/VDE Tripping characteristic/-class Test current I4, hold (x In) rated current In / IEC, DIN/VDE • at 30 Cel • at 40 Cel • at 45 Cel • at 45 Cel • at 50 Cel • at 55 Cel • at 60 Cel • at 60 Cel	Rated service short-circuit breaking capacity Ics		-
Tripping characteristic/-class Conventional tripping current I2, (x ln)	Rated ultimate short-circuit breaking capacity Icu		-
(x In) rated current In IEC, DIN/VDE Tripping characteristic/-class Test current I4, hold (x In) - rated current In / IEC, DIN/VDE A 6 • at 30 Cel A 5.64 • at 40 Cel A 5.418 • at 45 Cel A 5.19 • at 50 Cel A 4.968 • at 60 Cel A 4.74	Tripping characteristics Number		-
Tripping characteristic/-class Test current I4, hold (x In) rated current In / IEC, DIN/VDE • at 30 Cel A 6 • at 40 Cel A 5.64 • at 45 Cel A 5.418 • at 50 Cel A 5.19 • at 55 Cel A 4.968 • at 60 Cel A 4.74			•
rated current In / IEC, DIN/VDE • at 30 Cel A 6 • at 40 Cel A 5.64 • at 45 Cel A 5.418 • at 50 Cel A 5.19 • at 55 Cel A 4.968 • at 60 Cel A 4.74	rated current In IEC, DIN/VDE		-
 at 30 Cel at 40 Cel at 45 Cel at 50 Cel at 55 Cel at 60 Cel A 6 A 5.64 A 5.418 A 5.19 A 4.968 A 4.74 	Tripping characteristic/-class Test current I4, hold (x In)		
• at 40 Cel • at 45 Cel • at 50 Cel • at 55 Cel • at 60 Cel A 5.64 A 5.418 A 5.19 A 4.968 A 4.74	rated current In / IEC, DIN/VDE		
 at 45 Cel at 50 Cel at 55 Cel at 60 Cel A 5.418 A 5.19 A 4.968 A 4.74 	• at 30 Cel	Α	6
• at 50 Cel A 5.19 • at 55 Cel A 4.968 • at 60 Cel A 4.74	• at 40 Cel	Α	5.64
• at 55 Cel A 4.968 • at 60 Cel A 4.74	• at 45 Cel	Α	5.418
• at 60 Cel A 4.74	• at 50 Cel	Α	5.19
	• at 55 Cel	А	4.968
Resistance against shock / according to IEC 60068-2-27 150m/s² at 11ms half-sine	• at 60 Cel	Α	4.74
	Resistance against shock / according to IEC 60068-2-27		150m/s² at 11ms half-sine

Certificates/approvals:

General Product Approval



IMQ

KETI

ROSTEST





Declaration of Conformity

Shipping Approval

Manufacturer









other

other

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


 $\underline{\text{http://support.automation.siemens.com/WW/view/en/5SY6206-7/all}}$


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


 $\underline{\text{http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY6206-7}}$

CAx-Online-Generator

http://www.siemens.com/cax







last change: Nov 3, 2011