SIEMENS

Product data sheet LZX:PT570730



PLUG-IN RELAY, 4 CO CONTACTS, 230V AC, 6A, WIDTH 22.5MM

General technical details:				
Supply voltage frequency / for auxiliary and control current circuit / rated value				
• minimum	Hz	50		
• maximum	Hz	60		
type of voltage		AC		
Control supply voltage				
• at 50 Hz / at AC / rated value				
• minimum	V	230		
• maximum	V	230		
• at 60 Hz / at AC / rated value				
• minimum	V	230		
• maximum	V	230		
Number of NC contacts				
for auxiliary contacts		0		
Number of NO contacts				
for auxiliary contacts		0		
Number of change-over switches				
for auxiliary contacts		4		
Operating current / of the auxiliary contacts				
• at DC-13				

• at 24 V	А	6
• at AC-15		
• at 230 V	Α	4
Design of the switching function		changeover switch
• guided		No
Switching behaviour		monostable

Mechanical design:				
Design of the electrical connection		screw-type terminals		
Design of the relay operating mechanism		poled		
Product component / jumper socket		No		
Width	mm	22.5		
Height	mm	28		
Depth	mm	35		

Certificates/approvals:

General Product Approval

other

ROSTEST



Manufacturer

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

 $\underline{\text{http://www.siemens.com/industrial-controls/catalogs}}$

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

CAx-Online-Generator

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/LZX:PT570730/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZX:PT570730

last change: Oct 24, 2011