SIEMENS

Product data sheet LZS:RT4A4T30



PLUG-IN RELAY COMPACT UNIT AC 230, 2 CO CONTACT LED MODULE RED STANDARD PLUG-IN SOCKET SCREW TERMINAL

General technical details:		
Supply voltage frequency / for auxiliary and control current circuit / rated value		
• minimum	Hz	50
• maximum	Hz	60
type of voltage		AC
Control supply voltage		
• at 50 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230
• at 60 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230
Number of NC contacts		
• for auxiliary contacts		0
Number of NO contacts		
• for auxiliary contacts		0
Number of change-over switches		
• for auxiliary contacts		2
Operating current / of the auxiliary contacts		
• at AC-15		

• at 230 V	Α	2.5
Design of the switching function		changeover switch
• guided		No
Switching behaviour		monostable

Mechanical design:				
Design of the electrical connection		screw-type terminals		
Design of the relay operating mechanism		poled		
Product component / jumper socket		Yes		
Width	mm	15.5		
Height	mm	71		
Depth	mm	78		

Certificates/approvals:

General Product
Approval

other

ROSTEST Manufacturer

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/industrial-controls/mall

CAx-Online-Generator

http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/LZS:RT4A4T30/all

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ ...)$

 $\underline{\text{http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZS:RT4A4T30}$

last change: Oct 24, 2011