

Additional camera for ABUS EasyLook BasicSet

Art. no. PPDF17520

Page 1 of 2



- Extension for the ABUS EasyLook BasicSet; additional camera with high wireless range, reliable motion detection, intercom function, night vision, privacy zone masking and much more
- A total of 4 security cameras can be wirelessly connected to the monitor of the ABUS EasyLook BasicSet
- Very easy to use, even for subsequent commissioning; supply power to the additional camera, add it to the set monitor and the first live image will appear
- Inside and outside, the surveillance camera reliably detects people/animals thanks to its clever motion detection (integrated motion detector/passive infrared sensor, PIR for short, detects heat; camera software analyses for motion in parallel)
- Monitor immediately and automatically switches to alarm and recording mode (siren sound on the monitor can be switched on/off as required; insert standard microSD card with up to 128 GB for storage)
- Personal settings via monitor; deactivate audio/sound for recordings (GDPR/data protection compliant), image areas with/without recognition, schedules, privacy zones
- Clear night vision in black and white (via infrared LED) up to 15 metres, 3-megapixel camera resolution, zoom function, 82-degree viewing angle, camera protection class IP66 (weatherproof; protection against strong jets of water, dustproof)
- No further costs (no subscription, no cloud)

Up to 4 cameras per monitor Add up to 4 cameras to your ABUS EasyLook BasicSet. Commissioning an additional camera is just as easy as with the basic set and done in just a few steps. Just like the camera in the basic set, an additional camera reliably delivers video images day & night. The camera performs its job without internet/Wi-Fi, without an app and without a smartphone - all it needs is power. The video data and settings are securely encrypted and quickly transmitted wirelessly between the camera and the monitor of the basic set. Commissioning the additional camera is just as easy as with the basic set. A total of up to 4 cameras can be easily operated with one monitor; if needed, the screen displays all live images from the cameras simultaneously - with a simple finger gesture, it is possible to quickly switch between the "quad view" and individual camera images. So you always have a view of what is happening in your shop or around your home, whether at the entrance, in front of the garage, on the terrace or in the garden.

Additional camera for ABUS EasyLook BasicSet

Art. no. PPDF17520

Page 2 of 2

Technical Data:

Channel width	20 MHz
Color	Black
Compatible with Secvest	No
Compatible with wAppLoxx	No
Compatible with Smartvest	No
Vertical angle of view	42 °
Min. humidity	30
Basic event	PIR & Software + Motion Mask
Dimensions	(W x L x H) 61 x 161 x 77 mm
Resolution modes	2305 x 1296 (3MP)
Image sensor	1/3" CMOS
Focal length	4 mm
Frequency range	2,403 - 2,478 GHz
Wireless range	(Depending on installation) 20 - 50 m
Housing material	Plastic
Horizontal angle of view	82 °
IR LEDs	Yes
IR range (up to)	15 m
IR cut filter	Yes
Compatible with	PPDF17000
Loudspeaker	Yes
Power consumption	3,6 W
Max. resolution @ frame rate	2305 x 1296 @15fps
Max. operating temperature	50 °C

Max. humidity	90 %
Microphone	Yes
Min. operating temperature	-10 °C
Minimum illumination (color)	1 lx
Minimum illumination (IR)	0,1 lx
Net weight	0,3 kg
Optical wavelength	940 nm
PIR angle of view	85 °
PIR range	8 m
Private zones	4
IP protection class	66
Transmission power	20 dBm
Sensitivity	-88 dBm
DC voltage supply	12 V
Connector type	DC-plug: 5,5 x 2,1 mm
Day/night switching	Auto
Encryption	WPA2
Video compression	H.264+
White balance	Auto