

Cisco GLC-LH-SMD Compatible SFP Module - 1000BASE-LX/LH - 1GbE Single Mode Fiber SMF Optic Transceiver - 1GE Gigabit Ethernet SFP - LC 10km - 1310nm - DDM Cisco Firepower, ASR920, IE2000

Product ID: GLCLHSMDST



The GLCLHSMDST is a Cisco GLC-LH-SMD compatible fiber transceiver module that has been designed, programmed and tested to work with Cisco brand switches and routers. It delivers dependable 1 GbE connectivity over fiber cable, for 1000BASE-LX/LH compliant networks, with a maximum distance of up to 10 km (6.2 mi).

Technical Specifications:

• Wavelength: 1310 nm

• Maximum Data Transfer Rate: 1.25 Gbps

• Type: Single Mode / Multi Mode Fiber

• Connection Type: LC Connector

• Maximum Transfer Distance: 10 km (6.2 mi) - SM / 1 km (0.6 mi) - MM

• MTBF: 200,000 hours

• Power Consumption: Less than 1 Watt

• Digital Diagnostics Monitoring (DDM): Yes

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.



Certifications, Reports and Compatibility













Applications

- Replacing defective or damaged SFP modules in Cisco switches and routers
- Expand your network to remote segments

Features

- 100% CISCO GLC-LH-SMD COMPATIBLE: Works with Cisco switches like Firepower, ASR920, IE2000, IE4000, ASR1000 and others
- TECHNICAL SPECS: 1000BASE-LX/LH 1 Gbps Single Mode (SMF)/Multi Mode (MMF) LC Connector 1310nm Digital Diagnostic Monitoring (DDM) Distances up to 10km (6.2mi)
- TESTED FOR OEM HOST COMPATIBILITY: Hot-swappable in Cisco routers and switches; DDM support reports the transceiver's status to most SNMP network management tools
- WORKS WITH MSA COMPLIANT SWITCHES: Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules
- THE IT PRO'S CHOICE: Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance.

Lifetime

Hardware			

Warranty

Compatible Brand Cisco

Industry Standards IEEE 802.3z 1000BASE-LX/LH

Performance

Maximum Data Transfer 1.25 Gbps

Rate

Max Transfer Distance 10 km (6.2 mi) - SM / 1 km (0.6 mi) - MM

Type Single Mode / Multi Mode

Wavelength 1310nm



Fiber Operating Mode Full-Duplex

DDM Yes

Compatible Networks 1000 Mbps (1 Gbps)

MTBF 200,000 hours

Power Consumption (In

Watts)

< 1 W

Connector(s)

Local Unit Connectors 1 - Fiber Optic LC Duplex

Special Notes / Requirements

Note For use in Gigabit fiber networking equipment and media

converters

Environmental

Operating Temperature 0C to 70C (32F to 158F)

Storage Temperature -40C to 85C (-40F to 185F)

Humidity 5~95% RH

Physical Characteristics

Product Length 2.3 in [58.0 mm]

Product Width 0.5 in [12.0 mm]

Product Height 0.3 in [0.8 cm]

Weight of Product 0.6 oz [18.0 g]

Packaging Information

Package Length 4.6 in [11.8 cm]

Package Width 3.6 in [92.0 mm]

Package Height 1.3 in [32.0 mm]

Shipping (Package)

Weight

3.4 oz [95.0 g]

What's in the Box



Included in Package

1 - SFP transceiver

*Product appearance and specifications are subject to change without notice.