

WI-FI 6 REPEATER AX1800

Upgrade your Wi-Fi network!



Fast and reliable, seamless Wi-Fi is where you need it!

STRONG's REPEATERAX 1800 is the quantum leap for households with high appliance density. With the Wi-Fi 6 it is the perfect solution to extend the coverage of your modem or router in just minutes. At a maximum speed of 1800 Mbit/s, the REPEATERAX 1800 is a compact wall plug solution designed for an extremely convenient placement.

The system of 2 adjustable external antennas combined with a smart LED System for an optimum positioning of the repeater will boost a wide and reliable Wi-Fi coverage throughout your home. Extend your Wi-Fi to the furthest corners of your home and garden and experience all the benefits of the new Wi-Fi generation. Stream, play and surf faster than ever with coverage for your entire home.

The Wi-Fi 6 REPEATERAX 1800 can also be configured as an outstanding 802.11ax wi-Fi 6 Access Point to immediately improve the Wi-Fi of your existing single band modem without exchanging it by a new one. Enjoy maximum security with WPA2 and the latest WPA3 wireless security protocols.

Performance



- IEEE 802.11ax Wi-Fi 6 standard
- Speed up to 1800 Mbit/s
- Backward compatible with Wi-Fi 5 and Wi-Fi 4 standards
- 574 Mbit/s @ 2.4 GHz & 1201 Mbit/s @ 5GHz
- Repeater/Access Point/ operational modes
- Works with any standard modem or router

Coverage & Reliability



- 2x adjustable external antennas for maximum coverage and reliability
- Smart LED system for an optimum positioning of the repeater

Security



- WPA/WPA2/ WPA3 for the highest level of Wi-Fi security
- Connect & Secure button for an easy set up and a maximum network security
- Power on/off button

Connections



1x Gigabit Ethernet WAN/LAN port



WI-FI 6 REPEATER AX1800

Wi-Fi

Frequency 2.4 GHz & 5GHz (11ax)

Standards IEEE 802.11ax /IEEE 802.11ac /IEEE

802.11n/IEEE 802.11g /IEEE 802.11a/

IEEE 802.11b

Signal Rate 5GHz: Up to 1201 Mbps

2.4GHz: Up to 574 Mbps

Security WPA-PSK/WPA2-PSK/WPA3

Antenna 2x 5dBi

Transmit Power CE: <20dBm(2.4 GHz), <23dBm

(5.15 GHz~5.25 GHz)

Supported Channels 2.4GHz: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11,

12, 13

5 GHz: 36, 40, 44, 48, 52, 56, 60, 64, 100,

104, 108, 112

Hardware

Ethernet Ports 1x 10/100/1000 Mbps self-adaptive

LAN

Buttons Reset Button / WPS Button

LEDs WiFi / WPS / Power

Power Direct plug-in power supply

(100V-240V)

Software

Configuration Wizards Repeater, Access Point

DHCP Auto, Server, Client

Management Web User Interface, Time Settings,

Configuration Backup/Restore,

Firmware Upgrade

Internet Protocol IPv4

Other specifications

Certification CE

Package contents REPEATERAX1800

Installation instructions

Warranty Card

System requirements Windows 7, 8, 8.1, 10, Mac OS X, Linux,

Internet Browser

Environment Operating temperature: 0° C ~ +40° C

Storage temperature: -40° C $\sim +70^{\circ}$ C Operating humidity: $10\%\sim90\%$ non-

condensing

Storage humidity: 5%~90% non-

condensing


77.8 x 49 x 130 mm

Size $(W \times D \times H)$

Size with antenna

(W x D x H) 77,8 x 49 x 222,8 mm

Weight: 0.29 kg



REPEATERAX1800 EAN: 9120072376825

PCB: 10