

WWW.DYNATRON-CORP.COM

Product Spec Sheet

B11



Application:

- Recommend for Intel® Xeon® Platinum / Gold Family Processor (Products formerly Skylake), Socket FCLGA3647
- For Narrow ILM Only
- Active Cooler for 3U Server and up

Overall Specification:

• Dimension: 108 x 80 x 110 mm

Weight: 600 g

Material: Aluminum Heatsink with Heatpipe Embedded

8025 Axial PWM Fan for Heat Exhausting

Convenient Heat Sink Screw captive mounting

Thermal Grease Shin-Etsu 7762 Pre-printed

Support CPU power up to 205 Watts heat dissipation

Includes both Fabric and Non-Fabric Package Carriers

Fan Specification:

Model Number: DF128025BM-PWM

Dimension: 80 x 80 x 25 mmBearing: Ball Type, Double

• Rated Voltage: 12V

Rated Speed:

At Duty Cycle 0~20%: 1000 ± 200 RPM
At Duty Cycle 50%: 2300 ± 10% RPM
At Duty Cycle 100%: 4000 ± 10% RPM

Rated Input Power:

At Duty Cycle 0~20%: 0.96 W
At Duty Cycle 50%: 1.44 W
At Duty Cycle 100%: 4.8 W

· Rated Airflow:

At Duty Cycle 0~20%: 12.5 CFM
At Duty Cycle 50%: 28.8 CFM

At Duty Cycle 100%: 50.0 CFM