



550 | 650 | 750W
MARBLEBRON

MARBLEBRON



- 80 PLUS® Bronze Certification
- A strong 12V rail with DC-DC-Design
- Semi-modular Flat Cables
- Japanese 105°C Electrolytic Capacitors
- 120mm High Pressure fan



The MARBLEBRON is a semi-modular power supply with high functionality and sophisticated design. It is 80 PLUS® Bronze certified and has first-class Japanese 105°C electrolytic capacitors for excellent reliability. Equipped with DC-to-DC technology, it ensures a stable power output even under alternating loads. The 120 mm high-pressure fan is kept at a constant low speed with a silent 14 dB(A) with the integrated SAC (Smart Air Control) up to a load of 40%. The MARBLEBRON is perfectly suited for mainstream gaming, multimedia and home theater systems.

Features


- 80 PLUS® Bronze certification with 88% efficiency in the 230-volt network at 50% system load
- Semi-modular design with flexible black flat cables for easy cable management
- A strong 12V rail with up to four PCI-E connectors for multiple graphics cards
- DC-to-DC design for a clean output voltage
- Efficient +5V circuit for a standby consumption of the entire system of less than 0.5W
- Active PFC designs with PF value up to 0.99
- High-quality components and first-class Japanese 105°C electrolytic capacitors
- 120 mm high-pressure fan with compressed airflow for faster cooling
- SAC (Smart Air Control), silent fan rotation with 14dB(A) to 40% load
- The multiple protection circuit with protection against overvoltage (OVP), undervoltage (UVP), overload (OPP), short circuit (SCP), overheating (OTP) and unexpected power surges (SIP)




Semi-modular Design




Flexible Flat Cable Design



80 PLUS® Bronze Certification




120mm High Pressure Fan



SAC (Smart Air Control) Design

Dimension

Unit: mm



Cables & Connectors

Model	Native Cables			Modular Cables		
	Mainboard 24P	CPU 4+4P (8P)	PCI-E 6+2P (8P)	SATA	4P Molex	FDD (Adapter)
750W	1	2	4	8	4	1
650W	1	1	4	8	4	1
550W	1	1	2	6	4	1

Specifications

Model		EMB550AWT		EMB650AWT		EMB750EWT	
AC Input Voltage		100-240VAC, 47-63Hz					
AC Input Current		8-4A		10-5A		11-5.5A	
DC Output							
		Rated	Combined	Rated	Combined	Rated	Combined
+3.3V		20A	110W	20A	120W	20A	130W
+5V		20A		20A		20A	
+12V1		45A	540W	54A	648W	62A	744W
-12V		0.3A	3.6W	0.3A	3.6W	0.3A	3.6W
+5Vsb		2.5A	12.5W	2,5A	12.5W	2.5A	12.5W
Total Power		550W		650W		750W	
Dimensions		150(B) x 86(H) x 140(T)mm					
        							
Logistic Information							
Model		EMB550AWT		EMB650AWT		EMB750EWT	
Bar Code	EAN	4713157724977		4713157724984		4713157724991	
	UPC	819315024973		819315024980		819315024997	
Box Dimension		248 x 211 x 95 mm					
Gross Weight / Unit		1.9 kg		2.2 kg		2.3 kg	
Carton Dimension		495 x 263 x 231 mm					
Q'ty / Carton		5 pcs					
Gross Weight / Carton		10.2 kg		11.3 kg		11.9 kg	