



# Ledinaire SlimDownlight DN065B

## DN065B G3 LDNR LED10/CCT 10.5W D150 RD

The LEDINAIRE range contains a selection of popular off-the-shelf LED luminaires that come with the high Philips quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need

### Product data

General Information	
Light source colour	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	PSU [ Power supply unit]
Driver included	Yes
Optic type	110 [ Beam angle 110°]
Luminaire light beam spread	110°
Connection	Screw connection block 2-pole
Cable	Cable 0.2 m without plug
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	F [ For mounting on normally flammable surfaces]
CE mark	CE mark
Warranty period	3 years
Constant light output	No
Number of products on MCB (16 A type B)	280

EU RoHS compliant	Yes
-------------------	-----

Operating and Electrical	
Input Voltage	220 to 240 V
Input frequency	50 or 60 Hz
Inrush current	5.05 A
Power factor (min.)	0.9

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Housing material	Metal
Reflector material	Polycarbonate aluminium coated
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Optical cover/lens finish	Matt
Overall height	45 mm

# Ledinaire SlimDownlight DN065B

Overall diameter	175 mm
Colour	White
Dimensions (height x width x depth)	45 x NaN x NaN mm (1.8 x NaN x NaN in)

## Approval and Application

Ingress protection code	IP20 (front IP40)
Mech. impact protection code	IK03 [ 0.3 J]

## Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	1000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	90.00 lm/W
Init. Corr. Colour Temperature	4000 K
Init. Colour rendering index	80
Initial chromaticity	(IEC4000K, 0.38, 0.38) 5SDCM
Initial input power	11 W
Power consumption tolerance	+/-10%

## Over Time Performance (IEC Compliant)

Median useful life L70B50	25000 h
---------------------------	---------

Lumen maintenance at median useful life*	L65
50,000 h	

## Application Conditions


Ambient temperature range	-20 to +40 °C
Suitable for random switching	No

## Product Data

Full product code	871951432910200
Order product name	DN065B G3 LDNR LED10/CCT 10.5W D150 RD
	RD
EAN/UPC – product	8719514329102
Order code	32910200
SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
SAP material	929002664832
SAP net weight (piece)	0.210 kg




## Dimensional drawing




Cut-out hole diameter - L150mm

DN065B G3 LDNR LED10/CCT 10.5W D150 RD

## Photometric data



Downlight DN065C G3 LDNR CCT D150 RD-LDD



Downlight DN065C G3 LDNR CCT D150 RD-GUL

## Ledinaire SlimDownlight DN065B

