



Watering clock WT 2

3-way distributor incl. watering clock. The watering stops automatically once the selected time has lapsed (max. 120 minutes). With G1 tap connector and G3/4 reduction piece.

- 1 2 independent, adjustable water connections and 1 outlet with water timer
- Ideal for connecting three hoses to a single tap with G1 thread
- 3 Plastic thread
- Simple attachment to the tap

- 2 Smooth-running union joint
- Simple attachment to the tap

- 4 Includes tap adaptor and pre-filter
- For fast connection with the garden hose

TECHNICAL DATA AND EQUIPMENT





Watering clock WT 2

- Smooth-running union joint
- Plastic thread for attachment to the tap
- Includes tap adaptor and pre-filter
- Watering up to 120 min
- Watering stops on expiry of a preset time

Technical data		
Order no.		2.645-209.0
EAN code		4039784620278
Weight	kg	0.4
Dimensions (L × W × H)	mm	92 × 225 × 200
		When connecting these products to the drinking water network, you must observe the requirements of EN 1717. If necessary, ask your sanitary specialist.

ACCESSORIES FOR WATERING CLOCK WT 2 2.645-209.0









		Order no.			Price	Description	
Kärcher Rain System®							
Kärcher Rain Box	1	2.645-238.0				The extendable Kärcher Rain Box with filter, drip collars, connection parts and hoses is the ideal ready-for-connection starter set for efficient garden watering.	ו 🗆
Sprinklers							
Oscillating sprinkler OS 3.220	2	2.645-133.0				Oscillating sprinkler OS 3.220 for watering medium-sized and large areas and gardens. Infinite coverage adjustment. Extremely durable gear drive. Maximum coverage: 220 m2	
Hose connection systems							
Universal Hose Connector with Aqua Stop	3	2.645-192.0				Universal hose coupling with Aqua Stop. Ergonomic design for convenient handling.	
Universal Hose Connector	4	2.645-191.0				Ergonomically designed universal hose coupling for convenient handling.	
Hoses							
PrimoFlex* hose - 1/2" 20 m	5	2.645-138.0				The PrimoFlex* (1/2") flexible garden hose is 20 m long, temperature-resistant, comes with pressure-resistant reinforcement technology and contains no substances that are harmful to health. Bursting pressure: 24 bar.	

[☐] Available accessories.