



Delock Adapter USB 2.0 Type-A male > 1 x Serial RS-232 RJ45 male 3.0 m blue

Description

This USB 2.0 to RS-232 adapter by Delock is suitable for the console at CISCO routers, switches, access points and other compatible devices via PC or laptop.



ltem no. 63289

EAN: 4043619632893

Country of origin: China

Package: Poly bag

Adapter

Specification

Connectors:

- 1 x USB 2.0 Type-A male
- 1 x serial RS-232 RJ45 male
- Chipset: FTDI FT232RL
- Signals: RTS(1), DSR(2), RXD(3), GND(4), GND(5), TXD(6), DTR(7), CTS(8)
- Compatible with USB 3.0, USB 2.0, and USB 1.1 full speed 12 Mbps
- Data transfer rate up to 230.4 Kb/s
- · Cable length: ca. 3.0 m
- Suitable for various compatible CISCO devices

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 2.6
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 1 x serial adapter
- User manual

Images



		USB 2.0 Type-A male	sarial R5-222 RJAS maile		1¢1
--	--	---------------------	--------------------------	--	-----





General	
Function:	Plug & Play
Specification:	RS-232
	USB 1.1
	USB 2.0
Supported operating system:	Mac OS 10.9
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	ex Linux Kernel 2.6.x
Interface	
Connector 1:	1 x USB 2.0 Type-A male
Connector 1: Connector 2:	1 x USB 2.0 Type-A male 1 x RJ45 plug
Connector 2:	
Connector 2: Technical characteristics	1 x RJ45 plug
Connector 2: Technical characteristics Chipset:	1 x RJ45 plug FTDI FT232RL
Connector 2: Technical characteristics Chipset: Data transfer rate:	1 x RJ45 plug FTDI FT232RL up to 230.4 Kb/s
Connector 2: Technical characteristics Chipset: Data transfer rate:	1 x RJ45 plug FTDI FT232RL up to 230.4 Kb/s 128 byte
Connector 2: Technical characteristics Chipset: Data transfer rate: FIFO:	1 x RJ45 plug FTDI FT232RL up to 230.4 Kb/s 128 byte 256 Byte
Connector 2: Technical characteristics Chipset: Data transfer rate: FIFO:	1 x RJ45 plug FTDI FT232RL up to 230.4 Kb/s 128 byte 256 Byte asynchronous
Connector 2: Technical characteristics Chipset: Data transfer rate: FIFO: Data transmission:	1 x RJ45 plug FTDI FT232RL up to 230.4 Kb/s 128 byte 256 Byte asynchronous