

DIGITUS 8K DisplayPort Connection Cable Version 1.4

DB-340201-010-S
EAN 4016032481232



PREMIUM DP1.4CABLE DP to DP 8K/60Hz, 1m Aluminum Housing ,Gold plated, Support 8K/60HZ

With this cable standard, the DisplayPort cable supports all current requirements – from the transmission of high-resolution UHD 8K content, 8-channel audio transmission and support of HDCP and DPCP encryption. Mirror your notebook desktop onto a large monitor or expand your desktop with an additional display using DisplayPort. High-speed data transfer is possible with this high-quality cable, no judder even during the most demanding graphics applications or games. Gold-plated contacts and double shielding of the cable ensure maximum conductivity and interference-free transmission.

The Digitus® 8K DisplayPort Connection Cable Version 1.4 already meets the requirements for future high-definition devices (TV, projector, monitor) of the next generation. The ultimate 8K experience with Ultra-HD II resolutions of up to 7680 x 4320 and high speed (32.4 Gbps) with a refresh rate of 60 Hertz

- Resolution: 7680 x 4320p / 60 Hz (UHD-2)
- Supports 8K 3D
- Data transfer rate of up to 32.4 Gbps (max. bandwidth)
- Supports up to 120Hz at 4K & Full HD (1080p)
- Subsampling: YUV 4:4:4
- HDCP version: 2.2
- DisplayPort™ version: 1.4
- Supported color depth: 16 Bit Deep Color
- Supports HDR
- Supports Consumer Electronic Control (CEC)
- Supports Lip Sync (audio/video synchronization)
- Supports stereoscopic 3D video
- Supports Display Stream Compression 1.2 (DSC)
- Supports EDID 2.0 (device recognition)
- Supports DVI Version 1.0 (in conjunction with adapters)
- Supports forward error correction (FEC)
- Multi Stream audio/video support
- Supports 21:9 Cinemascope

- 32 channel audio support
- Dolby TrueHD capable
- Supports 8-channel LPCM, 192 kHz, 24-bit audio capability
- Supports DTS-HD Master Audio bitstream
- Supports Super Audio CD (DSD)
- Supports DVD audio
- Supports Blu-ray Disc and HD DVD audio and video
- Cable diameter: 6.8 mm
- OM version: OM3
- Operating temperature: -20 ~ 60°C
- Operating humidity: 0 - 95% RH
- Connection 1: DP, Plug
- Connection 2: DP, Plug
- Connection 2: DP, Plug
- Locking mechanism: Snap-in fastening
- AWG: 30
- DisplayPort standard: DisplayPort 1.4
- Cable color: black
- Hood: Aluminum housing
- HDTV standard: Ultra HD 8K
- Contact surface: gold-plated
- Length: 1 m
- AOC - Active Optic Cable: no
- Shielding: double shielding
- Connector surface: gold-plated
- Color cable: black
- Shielding: Double shielding
- Connector 1: DP, plug
- Connector 2: DP, plug
- DisplayPort standard: DisplayPort 1.4
- Ferrite filter: none
- AOC - Active Optical Cable: no
- HDTV Standard: Ultra HD 8K
- Length: 1 m

Package contents

- 8K DisplayPort Connection Cable Version 1.4 (1 m)

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 60 | 5.94 | 33.00 | 49.00 | 31.00 | 50,127.00 |
| Packaging Unit Inside | 1 | 0.10 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Single | 1 | 0.10 | 16.00 | 16.00 | 3.00 | 768.00 |
| Net single without Packaging | 1 | 0.08 | 21.00 | 23.00 | 2.00 | 966.00 |

More images:

