

Philips Gaming Monitor Full HD gaming monitor

Momentum 3000

27" (68.5 cm) 1920 x 1080 (Full HD)

27M1N3200VS

# Take gaming to the next level

This Philips gaming monitor is an ideal all-around display for intense PC games. Sync technology, rapid 165 Hz refresh rate and 1 ms response time deliver smooth gameplay. Includes a visually immersive slim-frame display and Ultra Wide-Color.

#### The gaming advantage is yours

- 165 Hz refresh rates for ultra-smooth, brilliant images
- 1 ms (MPRT) fast response for crisp images and smooth gameplay
- · Low input lag reduces time delay between devices to monitor
- · SmartImage game mode optimised for gamers

## Immersive visuals

- VA display delivers awesome images with wide viewing angles
- 16:9 Full HD display for crisp, detailed images
- Ultra Wide-Color wider range of colours for a vivid picture
- SmartContrast for rich black details

## Features designed for you

- · LowBlue mode and Flicker-free easy-on-the eyes viewing
- Built-in stereo speakers for multimedia
- EasySelect menu toggle key for quick on-screen menu access



# Highlights

#### 165 Hz Gaming




You play intense, competitive gaming. You demand display with lag free, ultra-smooth images. This Philips display redraws the screen image up to 165 times per second, effectively faster than a standard display. A lower frame rate can make enemies appear to jump from spot to spot on the screen, making them difficult targets to hit. With 165 Hz frame rate, you get those critical missing images on the screen which shows enemy movement in ultrasmooth motion so you can easily target them. With ultra-low input lag and no screen tearing, this Philips display is your perfect gaming partner

#### 1 ms MPRT fast response



MPRT (motion picture response time) is a more intuitive way to describe response time, which directly refers to the duration between seeing blurry noise and clean, crisp images. The Philips gaming monitor with 1 ms MPRT effectively eliminates smearing and motion blur and delivers sharper and more precise visuals to enhance your gaming experience. The best choice for playing thrilling and twitch-sensitive games.

#### **Low Input Lag**



Input lag is the amount of time that elapses between performing an action with connected devices and seeing the result on screen. Low input lag reduces the time delay between entering a command from your devices to monitor, greatly improving play on twitch-sensitive video games, particularly important for playing fast-paced, competitive games.

### SmartImage Game mode



The new Philips gaming display has quick-access OSD fine-tuned for gamers, offering you multiple options. "FPS" mode (First person shooting) improves dark themes in games, allowing you to see hidden objects in dark areas. "Racing" mode adapts the display with the fastest response time and high colour, along with image adjustments. "RTS" mode (Real-time strategy) has a special SmartFrame mode that enables highlighting of specific area and allows for size and image adjustments. Gamer 1 and Gamer 2 enable you to save personal customised settings based on different games, ensuring best performance.

#### **VA** display



The Philips VA LED display uses an advanced multi-domain vertical alignment technology that gives you super-high static contrast ratios for extra-vivid and bright images. While standard office applications are handled with ease, it is especially suitable for photos, web browsing, films, gaming and demanding graphical applications. Its optimised pixel management technology gives you a 178/178 degree extra-wide viewing angle, resulting in crisp images.

#### LowBlue Mode and Flicker-free



Our LowBlue Mode and Flicker-free technology have been developed to reduce eye strain and fatigue often caused by long hours in front of a monitor.

# **Built-in stereo speakers**



A pair of high-quality stereo speakers built into a display device. They may be visible front firing, or invisible down firing, top firing, rear firing etc. depending on model and design.





















# **Specifications**

#### Picture/Display

- LCD panel type: VA LCD
- · Backlight type: W-LED system
- Panel Size: 27 inch / 68.5 cm
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
  Effective viewing area: 597.888 (H) x 336.312 (V)
- · Aspect ratio: 16:9
- Maximum resolution: 1920 x 1080 @ 165 Hz\*
- Pixel Density: 81.59 PPI
- Response time (typical): 4 ms (Grey to Grey)\*
- MPRT: 1 ms
- · Low Input Lag
- Brightness: 250 cd/m<sup>2</sup>
- SmartContrast: Mega Infinity DCR
- Contrast ratio (typical): 3000:1
- Pixel pitch: 0.3114 x 0.3114 mm
- Viewing angle: 178° (H)/178° (V), @ C/R > 10
- Colour gamut (typical): NTSC 101.5%\*, sRGB 121.9%\*, Adobe RGB 89.9%\*
- · Picture enhancement: SmartImage game
- Display colours: 16.7 M
- Scanning Frequency: HDMI: 30 160 kHz (H) / 48 - 165 Hz (V); DP: 30 - 200 kHz (H) / 48 - 165 Hz
- LowBlue Mode
- EasyRead
- sRGB
- · Adaptive sync

#### Connectivity

- Signal Input: HDMI 2.0 x 2, DisplayPort 1.2 x 1
- HDCP: HDCP 1.4 (HDMI / DP); HDCP 2.2 (HDMI
- Audio (In/Out): Audio out
- Sync Input: Separate Sync

# Convenience

- Built-in Speakers: 5 W x 2
- · User convenience: Power On/Off, Menu/OK, Input/Up, Game Settings/Down, SmartImage game/
- · OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian
- · Other convenience: Kensington lock, VESA mount  $(100 \times 100 \text{ mm})$
- Plug and Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7

#### **Stand**

• Tilt: -5/20 degree

#### **Power**

- On mode: 25.0 W (typ.)
- Standby mode: 0.5 W (typ.)
- Off mode: 0.3 W (typ.)
- · Energy Label Class: F
- Power LED indicator: Operation White, Standby mode - White (flashing)
- Power supply: Internal, 100-240 VAC, 50-60 Hz

#### **Dimensions**

- · Product with stand (max height): 614 x 447 x 193 mm
- Product without stand (mm): 614 x 365 x 55 mm
- Packaging in mm (W x H x D): 780 x 525 x 186 mm

#### Weight

- Product with stand (kg): 5.52 kg
- Product without stand (kg): 3.80 kg
- Product with packaging (kg): 9.48 kg

# **Operating conditions**

- Temperature range (operation): 0°C to 40 °C
- Temperature range (storage): -20°C to 60 °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000 ft (3658 m), Nonoperation: +40,000 ft (12,192 m)
- MTBF: 50 000 (Excluded backlight) hour(s)

#### Sustainability

- · Environmental and energy: RoHS
- Recyclable packaging material: 100 %
- Specific Substances: Mercury free, PVC/BFR free

#### Compliance and standards

 Regulatory Approvals: CB, CE Mark, FCC Class B, ICES-003, CU-EAC, EAEU RoHS, TUV/ISO9241-307, TUV-BAUART

#### **Cabinet**

- Colour: Black
- Finish: Textured

# What's in the box?

- · Monitor with stand
- · Cables: HDMI cable, DisplayPort cable, Power cable
- User Documentation



Issue date 2022-06-14

Version: 2.1.1

12 NC: 8670 001 79909 EAN: 87 12581 78205 4 © 2022 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

- \* The maximum resolution works for either HDMI input or DP input.
- \* For best output performance, please always ensure that your graphic card is capable of achieving the maximum resolution and refresh rate of this Philips display.
- \* Response time value equal to SmartResponse \* MPRT adjusts the brightness for blur reduction, so the brightness cannot be adjusted while MPRT is turned on. To reduce motion blur, the LED backlight will strobe in time with the screen refresh rate,
- which may cause a noticeable change in brightness.

  \* MPRT is a gaming-optimised mode. Turning on MPRT may cause noticeable screen flickering. It is recommended to turn this mode off when you are not using the gaming function.
- \* NTSC Area based on CIE 1976 \* sRGB Area based on CIE1931

- \* Adobe RGB Coverage based on CIE 1976
  \* The monitor may look different from feature images.