

You've got the moves. We've got the views

Who wants to choose between speed and picture quality? Not you. So, enjoy the game with a refreshingly speedy 165Hz refresh rate¹. Silence choppy gameplay, permanently, with the 1ms response time with overdrive.¹





Fun just got faster

The NVIDIA® G-SYNC® Compatible³ OMEN 27i monitor is validated by NVIDIA to bring you smooth, tear-free gaming with a 165Hz refresh rate¹ and 1ms response time with overdrive¹. Fun just got fast. *Product image may differ from actual product

Colors for days

Nano IPS panel technology with QHD² resolution delivers extraordinary DCI-P3 98% color reproduction that fully immerses you into every game, with wider viewing angles and better contrast, to enhance your experience.

Get into position, in any position

Play comfortably—adjust the height easily and say goodbye to distracting bezels, plus ambient RGB lighting to help reduce eye strain.

Featuring

Step up to the best

IPS technology brings you clear views from almost any angle. Every seat is the best seat in the house.

1-millisecond response time with Overdrive

Eliminates motion blur for crisp, fluid gameplay no matter what's happening on-screen.¹

165Hz refresh rate

Crisp action and incredibly responsive gameplay with virtually no artifacting or screen tearing.¹

NVIDIA® G-SYNC® Compatible

Sharp, fluid, and stutter-free gaming with up to 165Hz refresh rates.¹

QHD Display

Ultra-sharp details and captivating definition with 3.7 million pixels.²

Height adjustment stand

Easily adjust your display to the most comfortable position with 130mm range of travel.

Ambient lighting

Diffused lighting to help reduce eye fatigue during late-night gaming sessions.

DCI-P3 color space

Get deeper hues and more accurate colors with a wider color gamut than sRGB.¹

Extensive port connectivity

HDMI, DisplayPort[™] and a USB 3.0 hub deliver advanced connectivity for the latest hardware and accessories.

Micro-edge display

Micro-edge design creates a larger viewing experience.

Share the panoramic view

Ultra-wide 178-degree viewing angles with consistent detail and vibrant color.

Anti-glare panel

Enjoy the sun and your favorite content with this anti-glare panel.







Productnumber	8AC94AA#ABB:; #A2N; #ABT; #ABU; #ABV; #ABY; #ACQ; #UUG; #UUZ
UPC number	194441004991
Display size	68.58 cm (27")
Display colors	1.07 bilion colors supported
Aspect ratio	16:9 ¹
Disp lay type	PS
Pixel pitch	0.233 mm
Responsetime	1ms GtG 1
Brightness	350 nits 1
Contrastratio	1000:11
Display contrastratio (dynamic)	1000000:1
Productcolor	Black
Resolution (maximum)	QHD (2560×1440@165Hz)
Resolutions supported	1024×768; 1280×1024; 1280×720; 1440×900; 1600×900; 1680×1050; 1920×1080; 1920×1200; 2560×1440; 640×480; 720×400; 720×480; 800×600
Display scan frequency (horizontal)	80-250 KHz
Display scan frequency (vertical)	48-144 Hz
Display features	Language selection; On-screen controls; Plug and Play; User controls; NVDIA G-SYNC **; Anti-glare
Display Input Type	1 DisplayPort™ 1.2 in (with HDCP support); 1 HDM12.0 (with HDCP support)
Physical security features	Security lock-ready ³
Environmental specifications	Arsenic-free display glass; Low halogen; Mercury-free display backlights ²
Energyefficiency	Energyefficiency class: 6; Annual energy consumption: 64 kWh;
Display User Control Options	Exit; Information; Input source; Language; Management; Menu; Power; Gaming; Image; Color
Operating temperature range	5 to 35°C
Op erating temperature range	41 to 95°F
Operating humidity range	20 to 80% non-condensing
Powersupply	Inputvoltage 100 to 240 VAC
VESAmount	100 mm x100 mm
Pixels per inch (ppi)	109 ppi
Panel bit depth	10bit
Vertical viewing angle	178*
Horizontal viewing angle	178*horizontal
Bezel	3-sided micro-edge
Tilt	-5 to +20*
Height adjustment range	130mm
Screen treatment	Anti-glare
Lowbluelightmodes	Yes
Port and Connectors	1 HDMI2.0; 1 DisplayPort ^w 1.2; 2 SuperSpeed USB Type-A 5Gbps signaling rate; 1 Line Output; 1 USB-B
HDCP	Yes, DisplayPort™and HDMI
Warranty	1 year parts and labour limited warranty.
Certifications and compliances	BIS; BSMt CB; CCC; CE; CECP; CEL; C-Tick; cTUVus; EAC; EUP Lot-5; FCC; ISO 13406-2 VDT Guidelines Approval; KC; KCC; NOM; RoHS; VCCI; WEEE; California Energy Commission (CEC); TUS-GS
What's in thebox	Monitor; DisplayPort™ cable; USB Type-A to B cable
Dimensions (LxW xH)	61.3 x 6.6 x 36.7 cm (Without stand.)
Weight	7.75 kg (With stand.)
Package Dimensions (LxW xH)	73 x 25 x 46 cm
Package weight	10.56 kg

Messaging Footnotes

 All performancespecifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.
QHD (Quad High Definition) content required to view QHD images.
Must support DisplayPort 1.2 directly from GPU. Requires GTX 650TiBoost GPU or higher. NVIDA R340 52 or higher. SeeNVIDA.com for more details.
FreeSync™ is only available when it is connected on DisplayPort™ or HDML FreeSync is an AMD® technology enabled on FHD or QHD displays and is designed to eliminate stuttering and/or tearing in games and videos by locking a display's refresh rate to the framerate of the graphics card. AMD Radeon Graphics and/or AMD A-Series APU-compliant monitors with DisplayPort/HDMIAdaptive-Sync required. AMD 15.11 Crimson driver (or never) required to support FreeSync over HDML Adaptive-fresh rates vary by monitor. Moreinformation is available at www.amd.com/freesync.

Technical Specifications Footnotes

¹ All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower ² External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen. ³ Lock is sold separately.

