

POWER UP



The Elite - v4 power supply unit is a dependable choice for entry level users and system integrators. The quiet 120mm fan, Active PFC, and 3 year warranty deliver a PSU that provides function and resilience you can count on. It's the perfect option for work horse systems stored and operated in less than ideal conditions and climates. This power supply unit has been engineered for reliability with a focus on reducing random shutdowns in conditions where power sources are inconsistent and unstable. The Elite - v4 is a complete solution, offering performance and stability at an affordable price.

FEATURES

Active PFC + Forward Topology Design : Constructed with protective measures normally found in high-end power supplies to increase safety and current stability.

High Temperature Resistance : Capable of operating at 40°C under full load allowing a longer lifespan in warmer environments.

Peak Power Tolerance : Can reliably push an additional 50W at peak power load for up to 10 seconds.

80 PLUS White EU 230V Efficiency : Maintains an average efficiency of 85% at typical load.

Durable, Reliable, and Safe : Will perform consistently in whatever environment whether it's high altitudes or ultra humid settings.

3 Year Warranty : This unit comes with a standard limited manufacturing warranty of 3 years from the date of purchase.

PACKAGE INFORMATION

Cable Type	EAN	UPC
US	4719512084458	884102056956
UK	4719512084465	884102056963
EU	4719512084472	884102056970
ST	4719512084489	884102056987
AU	4719512084496	884102056994
BR	4719512084502	884102057007
KR	4719512084519	884102057014
TW	4719512084526	884102057021
JP	4719512084533	884102057038
IN	4719512084540	884102057045
WO	4719512084557	884102057052

Nett Weight	0.002 kg / 0.004 lb		
Gross Weight	0.002 kg / 0.004 lb		
Package Dimensions	213 x 195 x 96mm (8.39 x 7.68 x 3.78")		
Carton Dimensions	500 x 228 x 215mm (19.69 x 8.98 x 8.46")		
Unit / Carton	5 pcs		
Carton / Pallet	50 pcs		

SPECIFICATIONS

Product Name	9	Elite 500 230V - v4			
Item Code		MPE-5001-ACABN			
ATX Version		ATX 12V Ver. 2.41			
PFC		Active PFC			
Input Voltage		200 - 240V			
Input Current		5A			
Input Frequer	псу	50 - 60Hz			
Dimensions (L x W x H)		140 x 150 x 86mm			
Fan Size		120mm			
Fan Bearing		Sleeve Bearing			
Efficiency		85% @ Typical Load			
80 PLUS Rating		80 PLUS White EU 230V			
ErP 2014 Lot 3		Yes			
Operating Temperature		40°C			
Power Good Signal		100 - 500 ms			
Hold Up Time		>14ms at 100% load			
MTBF		>100,000 hours			
Protections		OVP / OPP / OTP / SCP / UVP			
Regulatory		TUV / cTUVus / CE / BSMI / FCC / EAC /			
		RCM / KCC / CCC / CB			
Connectors	ATX 24 Pin	x1			
	EPS 4+4 Pin	x1			
	SATA	x5			
	Peripheral 4 Pin	x3			
	PCI-e 6+2 Pin	x2			

AC INPUT	200 - 240V~ 5A 50 - 60Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vstb
	14A	16A	38A	0.3A	ЗA
TOTAL POWER	110W		500W	3.6W	15W
	500W				