FLOW TO PRESSURE



FEATURES

New Air Balance Blade - Optimized fan blade design with increased curvature that improves air flow and air pressure.

Improved Frame Durability - Enhanced square frame structure with added rib-support for reducing turbulent flow, noise and increasing overall work efficiency.

New Bearing Sealant – Two-tier sealing mechanism designed to improve dustproof capabilities and prevent lubricant oil leakage for extended life span and performance.

Luminescent Light Effect– Using milky white tinted fan blades to enhance light dispersion for more vibrant and luminescent effect.

Certified Compatible with Asus Aura, ASRock RGB and MSI RGB Motherboards. (Both ARGB and RGB version)

PACKING INFORMATION

EAN code	4719512097434	
UPC code	884102069734	
Net weight	0.541	
Gross weight	0.659	
Package dimension (L x W X H)	133 x 88 x 198 mm	
Carton dimension (L x W x H)	465 x 363 x 303 mm	
Units/CTN	20	

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	7920	72	N/A
40′	15840	72	N/A
40 HQ	18480	84	N/A

Power Comes in Packs of There

Continuing the SickleFlow 120 series , Cooler Master introduces a few new models with brand new upgraded design features for enhanced performance. Introducing addressable RGB lighting more vibrant than before and certified compatible with all major motherboard manufacturers.

The new SickleFlow 120 fan blades were created with larger blades and increased curvature to optimize the air flow and air pressure performance. Strengthen structural frame design with added rib housing for durability. Improved dustproof and oil leakage prevention for beater life expectancy,

SPECIFICATIONS

Product Name	SickleFlow 120 ARGB 3in1
Product Number	MFX-B2DN-183PA-R1
Profile	Addressable RGB
Bearing Type	Rifle
Fan Speed (RPM)	650~1800 RPM ± 10%
Airflow (CFM)	62 CFM ± 10%
Air Pressure (mmH ₂ O)	2.5 mmH2O ± 10%
Fan Noise Level (dBA)	8~27 dBA
Dimensions (mm)	120 x 120 x 25 (4.7 x 4.7 x 1")
MTTF (hours)	160,000
RGB Connector	3-Pin ARGB
RGB Rated Voltage	5 VDC
RGB Rated Current	0.21 A
Rated Voltage	12 VDC
Rated Current	0.15 A
Safety Current	0.37A
Power Consumption	1.8 W
Connector	4-Pin PWM
Weight	156 g (0.34 lbs)
Warranty	2 Years



FEATURES



Better Structural Support

New Flange housing design with added rib for better support, reduced vibration and



New AB Fan Blades

Larger and more curved fan blades for optimized air flow and air pressure.



Two-Tier Sealing Mechanism

Improve dustproof properties as well as prevent sleeve lubricant from leaking.





Motherboard/Controller (Needed)

Requires Motherboard ARGB port or ARGB controller (included).