# Sandberg<sup>®</sup> Streamer USB Webcam Pro Elite





The Sandberg Streamer USB Webcam Pro is the perfect webcam for streaming, gaming and just talking to friends online. With its 1080P Full HD resolution and super sharp pictures at 30 FPS, or at a full 60 FPS with 1080P resolution. The camera also offers great features like autofocus and automatic light correction. The camera itself is placed in the center of a circle of lights, which are touch controlled. A noise-reducing stereo microphone is built into the camera ensuring optimal voice reproduction.



More information:
www.sandberg.world

### Sandberg Streamer USB Webcam Pro Elite

## Specifications

USB 2.0 interface Supports UVC Cable length: 2 metres Video resolution: 2560x1440P, 1920x1080P, 1280x720P, 640x480P Frame rate; 2560x1440P@30fps, 1920x1080P@60fps H.264, H265, JPEG, YUY2 ePTZ-function: Digital pan, tilt and 5 X zoom 76° viewing angle Built in privacy shutter Autofocus on/off Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions: Pan, tilt, zoom, mute, autofocus on/off, light adjust, flip up/down, mirror.	
Cable length: 2 metres Video resolution: 2560x1440P, 1920x1080P, 1280x720P, 640x480P Frame rate; 2560x1440P@30fps, 1920x1080P@60fps H.264, H265, JPEG, YUY2 ePTZ-function: Digital pan, tilt and 5 X zoom 76° viewing angle Built in privacy shutter Autofocus on/off Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	USB 2.0 interface
Video resolution: 2560x1440P, 1920x1080P, 1280x720P, 640x480P Frame rate; 2560x1440P@30fps, 1920x1080P@60fps H.264, H265, JPEG, YUY2 ePTZ-function: Digital pan, tilt and 5 X zoom 76° viewing angle Built in privacy shutter Autofocus on/off Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	Supports UVC
Frame rate; 2560x1440P@30fps, 1920x1080P@60fps H.264, H265, JPEG, YUY2 ePTZ-function: Digital pan, tilt and 5 X zoom 76° viewing angle Built in privacy shutter Autofocus on/off Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	Cable length: 2 metres
H.264, H265, JPEG, YUY2 ePTZ-function: Digital pan, tilt and 5 X zoom 76° viewing angle Built in privacy shutter Autofocus on/off Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	Video resolution: 2560x1440P, 1920x1080P, 1280x720P, 640x480P
H.264, H265, JPEG, YUY2 ePTZ-function: Digital pan, tilt and 5 X zoom 76° viewing angle Built in privacy shutter Autofocus on/off Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	Frame rate; 2560x1440P@30fps, 1920x1080P@60fps
76° viewing angle Built in privacy shutter Autofocus on/off Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	
Built in privacy shutter Autofocus on/off Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	ePTZ-function: Digital pan, tilt and 5 X zoom
Autofocus on/off Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	76° viewing angle
Built-in adjustable ring light Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	Built in privacy shutter
Built-in Omni-directional stereo microphones Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	Autofocus on/off
Mic sensitivity: -35db+, SNR65d2 Mic with noise reduction Remote control functions:	Built-in adjustable ring light
Mic with noise reduction Remote control functions:	Built-in Omni-directional stereo microphones
Remote control functions:	Mic sensitivity: -35db+, SNR65d2
	Mic with noise reduction
Pan, tilt, zoom, mute, autofocus on/off, light adjust, flip up/down, mirror.	
	Pan, tilt, zoom, mute, autofocus on/off, light adjust, flip up/down, mirror.

#### Seckaging info

1 Sandberg Streamer USB Webcam Pro Elite

- 1 Remote control 1 Cleaning cloth for lens
- 1 Quick guide

#### ← Dimensions

	Product	Package
Height (cm)		14.00
Width (cm)		11.50
Depth (cm)		6.30
Weight (g)		250.00

Product:

90

www.sandberg.world/product/streamer-usb-webcam-pro-elite

Sandberg<sup>®</sup>

Dealer: