This powerful Nilfisk with long-life induction motor easily handles larger and frequent cleaning tasks.

It offers good ergonomics and a large range of operation with its 9m soft hose or 10m steel armed hose. From gentle cleaning of more soft or sensitive surfaces to blasting away ingrained dirt.

It is equiped with many invaluable features, when you need to work for longer periods of time; telescopic handle, sturdy wheels, long hose and onehand operated hose reel as well as a rubber suspension to ensure lower noise.

To increase performance, this Nilfisk comes with Click&Clean connectivity for a range of optional accessories.

These machines offer a wide variety of benefits and features:

- 145 bar, max pressure
- Sturdy built with aluminum pump and long-life induction motor.
- Automatic start/ stop system
- 9m soft hose or 10 steelarmed hose
- One-hand operated hose reel
- Telescopic handle with sturdy and robust aluminum tubes
- Rubber suspension ensures a lower noise when working
- Easy storage of gun, lance, nozzles and foam sprayer onboard
- Click&Clean nozzle system ensures quick and easy change of nozzle.
- The X-TRA model features a built-in trolley for increased mobility.
- Can be used as stationary machine with optional wall hook

• Standard equipment

	Included accessories	Ref. no.	Min. required	E 145.4-9 X- TRA UK	E 145.4-9 P X-TRA UK	E 145.4-9 PA X-TRA UK
Hose and Co	nnection					
9	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•	•	•
Nozzle - High	Pressure Washer					
	C&C POWER SPEED	128501153	0	•	•	•
	TORNADO CC 4 DOTS DARK BLUE	128500854	0	•	•	•
Brush						
	ROTARY BRUSH	126411395	0			•
Accessory						
T	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0			



	Included accessories	Ref. no.	Min. required	E 145.4-9 X- TRA UK	E 145.4-9 P X-TRA UK	E 145.4-9 PA X-TRA UK
$\bigcirc$	DRAIN AND TUBE CLEANER ALTO	6410766	0			
	G4 NOZZLE TUBE SHORT	128500676	0	•	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	٠	•	•
6	NILFISK PATIO ACCESSORY	128500702	0		•	•
19	NILFISK POWER PATIO	128500955	0			

Standard equipment

	Included accessories	Ref. no.	Min. required	E 145.4-9 PAD X-TRA UK	E 145.4-9 POWER X- TRA UK	E 145.4-9 X- TRA EU
Hose and Co	nnection					
	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•	•	•
Nozzle - High	Pressure Washer					
	C&C POWER SPEED	128501153	0	•	•	•
	TORNADO CC 4 DOTS DARK BLUE	128500854	0	•	•	•
Brush						
	ROTARY BRUSH	126411395	0	٠		
Accessory						
	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0			



	Included accessories	Ref. no.	Min. required	E 145.4-9 PAD X-TRA UK	E 145.4-9 POWER X- TRA UK	E 145.4-9 X- TRA EU
$\bigcirc$	DRAIN AND TUBE CLEANER ALTO	6410766	0	•		
	G4 NOZZLE TUBE SHORT	128500676	0	•	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•	•	•
6	NILFISK PATIO ACCESSORY	128500702	0	٠		
19	NILFISK POWER PATIO	128500955	0		•	

Standard equipment

	Included accessories	Ref. no.	Min. required	E 145.4-9 P X- TRA EU	E 145.4-9 PA X-TRA EU	E 145.4-9 PAD X-TRA EU
Hose and Co	nnection					
	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•	•	•
Nozzle - High	Pressure Washer	1	1	1		
	C&C POWER SPEED	128501153	0	•	•	•
	TORNADO CC 4 DOTS DARK BLUE	128500854	0	•	•	•
Brush		1	1			
	ROTARY BRUSH	126411395	0		•	•
Accessory						
T	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0			•



	Included accessories	Ref. no.	Min. required	E 145.4-9 P X- TRA EU	E 145.4-9 PA X-TRA EU	E 145.4-9 PAD X-TRA EU
$\bigcirc$	DRAIN AND TUBE CLEANER ALTO	6410766	0			
	G4 NOZZLE TUBE SHORT	128500676	0	•	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•	•	•
2	NILFISK PATIO ACCESSORY	128500702	0	•	•	•
19	NILFISK POWER PATIO	128500955	0			

Standard equipment

	Included accessories	Ref. no.	Min. required	E 145.4-9 POWER X- TRA EU
Hose and Cor	nnection			
	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•
Nozzle - High	Pressure Washer			
	C&C POWER SPEED	128501153	0	٠
	TORNADO CC 4 DOTS DARK BLUE	128500854	0	•
Brush				
	ROTARY BRUSH	126411395	0	
Accessory				
	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•
9	DRAIN AND TUBE 8M	128500461	0	



	Included accessories	Ref. no.	Min. required	E 145.4-9 POWER X- TRA EU
$\bigcirc$	DRAIN AND TUBE CLEANER ALTO	6410766	0	
	G4 NOZZLE TUBE SHORT	128500676	0	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•
6	NILFISK PATIO ACCESSORY	128500702	0	
10	NILFISK POWER PATIO	128500955	0	•

The powerful, long-life,	lavvi mala a blada muanavi	سمالمماما سممامميني	fue and end and end	, ala andra a ta alva
	iow-noise nign-nressi	re washer ineal for	treatient or larger	

Ref. no.128471861284718812847190Technical specificationsPump pressure (bar/MPa)Max 145/ max 14.5Max 145/ max 14.5Max 145/ max 14.5Yotage (V)230 - 240230 - 240230 - 240Rated power (kW)2.12.12.1Power consumption (A)9.59.59.5Water flow Qmax/Qiec (l/h)500/ 420500/ 420500/ 420Hose length (m)999Max. inlet temperature (°C)404040Length xwidth x height (mm)395 x 345 x 900395 x 345 x 900395 x 345 x 900Model18.618.618.618.6Model128471192128471192128471192128471185Fer. no.128471192128471194128471185Technical specifications1200 - 230 - 240230 - 240230 - 240Yump pressure (bar/MPa)Max 145/ max 14.5Max 145/ max 14.5Max 145/ max 14.5Voltage (V)230 - 240230 - 240230 - 240230 - 240Yump pressure (bar/MPa)Max 145/ max 14.5Max 145/ max 14.5Max 145/ max 14.5Voltage (V)230 - 240230 - 240230 - 240230 - 240Yump pressure (bar/MPa)212.12.12.1Power (kW)212.12.12.12.1Power (col)39.59.59.59.59.5	Model	E 145.4-9 X-TRA UK	E 145.4-9 P X-TRA UK	E 145.4-9 PA X- TRA UK
Pump pressure (bar/MPa)         Max 145/ max 14.5         Max 145/ max 14.5         Max 145/ max 14.5           Voltage (V)         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1           Power consumption (A)         9.5         9.5         9.5           Vater flow Qmax/Qiec (l/h)         500/ 420         500/ 420         500/ 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6         18.6           Model         128471192         128471194         128471185           Fer. no.         128471192         128471194         128471185           Pump pressure (bar/MPa)         Max 145/ max 14.5         Max 145/ max 14.5         300 - 240           Voltage (V)         230 - 240         230 - 240         230 - 240         230 - 240	Ref. no.	128471186	128471188	128471190
Voltage (V)         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1           Power consumption (A)         9.5         9.5         9.5           Water flow Qmax/Qiec (l/h)         500/ 420         500/ 420         500/ 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6           Model         128471192         128471182         128471185           Fer. no.         128471192         128471184         128471185           Pump pressure (bar/MPA)         Max 145/ max 14.5         Max 145/ max 14.5           Voltage (V)         230 - 240         230 - 240         230 - 240           Ret dp ower (kW)         2.1         2.1         2.1	Technical specifications			
Rated power (kW)         2.1         2.1         2.1           Power consumption (A)         9.5         9.5         9.5           Water flow Qmax/Qiec (l/h)         500/ 420         500/ 420         500/ 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6           Model         E145.4-9 PAD X         E145.4-9 POWER         E145.4-9 PAD X           Ref. no.         128471192         128471194         128471185           Technical specifications         128471192         128471194         128471185           Votage (V)         230 - 240         230 - 240         230 - 240           Ret dopwer (kW)         2.1         2.1         2.1	Pump pressure (bar/MPa)	Max 145/ max 14.5	Max 145/ max 14.5	Max 145/ max 14.5
Power consumption (A)         9.5         9.5         9.5           Water flow Qmax/Qiec (I/h)         500/ 420         500/ 420         500/ 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6           Model         12847 1192         12847 1194         12847 1185           Ref. no.         12847 1192         12847 1194         12847 1185           Pump pressure (bar/MPa)         Max 145/ max 145,	Voltage (V)	230 - 240	230 - 240	230 - 240
Water flow Qmax/Qiec (l/h)         500/ 420         500 / 420         500 / 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6           Model         12847 PADX         \$12847 PADX         \$12847 PADX           Ref. no.         12847 T192         12847 T192         12847 T192           Pump pressure (bar/MPa)         Max 145/ max 14.5         Max 145/ max 14.5           Yotage (V)         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1	Rated power (kW)	2.1	2.1	2.1
Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6           Model         128471192         128471192         128471185           Ref. no.         128471192         128471192         128471185           Pump pressure (bar/MPA)         Max 145/ max 14.5         Max 145/ max 14.5         Max 145/ max 14.5           Votage (V)         230 - 240         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1         2.1	Power consumption (A)	9.5	9.5	9.5
Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6           Model         E 145.4-9 PADX repower         E 145.4-9 POWER         E 145.4-9 POWER           Ref. no.         128471192         128471194         128471185           Technical specifications         Voltage (V)         Max 145/max 14.5         Max 145/max 14.5           Rated power (kW)         2.1         2.1         2.1	Water flow Qmax/Qiec (I/h)	500/ 420	500/ 420	500/ 420
Length x width x height (mm)       395 x 345 x 900       395 x 345 x 900       395 x 345 x 900         Weight (kg)       18.6       18.6       18.6         Model       E 145.4-9 PADX-       E 145.4-9 POWER K-TRA UK       E 145.4-9 POWER K-TRA UK       E 145.4-9 POWER K-TRA UK         Ref. no.       128471192       128471194       128471185         Technical specifications       Voltage (V)       Max 145/ max 14.5       Max 145/ max 14.5         Rated power (kW)       2.1       2.1       2.1	Hose length (m)	9	9	9
Weight (kg)18.618.618.6ModelE 145.4.9 PAD X TRA'UKE 145.4.9 PAUK R S 12847192E 145.4.9 X-TRA'UKRef. no.128471192128471194128471185Technical specificationsVoltage (V)Max 145/ max 14.5 230 - 240Max 145/ max 14.5 230 - 240Max 145/ max 14.5 230 - 240Red power (kW)2.12.12.1	Max. inlet temperature (°C)	40	40	40
ModelE 145.4-9 PAD X- E 145.4-9 POWER K-TRA UKE 145.4-9 X-TRA EURef. no.128471192128471194128471185Technical specifications128471192128471194128471185Pump pressure (bar/MPa)Max 145/max 14.5Max 145/max 14.5Max 145/max 14.5Voltage (V)230 - 240230 - 240230 - 240Rated power (kW)2.12.12.1	Length x width x height (mm)	395 x 345 x 900	395 x 345 x 900	395 x 345 x 900
Model         TRA UK         X-TRA UK         TEU           Ref. no.         128471192         128471194         128471185           Technical specifications         Max 145/ max 14.5         Max 145/ max 14.5         Max 145/ max 14.5           Pump pressure (bar/MPa)         Max 145/ max 14.5         Max 145/ max 14.5         Max 145/ max 14.5           Voltage (V)         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1	Weight (kg)	18.6	18.6	18.6
Max 145/ max 14.5         Max 145/ max 14.5         Max 145/ max 14.5           Pump pressure (bar/MPa)         Max 145/ max 14.5         Max 145/ max 14.5         Max 145/ max 14.5           Voltage (V)         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1	Model			
Pump pressure (bar/MPa)         Max 145/ max 14.5         Max 145/ max 14.5         Max 145/ max 14.5           Voltage (V)         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1	Ref. no.	128471192	128471194	128471185
Voltage (V)         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1	Technical specifications			
Rated power (kW)         2.1         2.1         2.1	Pump pressure (bar/MPa)	Max 145/ max 14.5	Max 145/ max 14.5	Max 145/ max 14.5
	Voltage (V)	230 - 240	230 - 240	230 - 240
Power consumption (A) 9.5 9.5 9.5	Rated power (kW)	2.1	2.1	2.1
	Power consumption (A)	9.5	9.5	9.5



Ren.128471192128471192128471192128471192Technical specificationsWater flow QmaxiQiec (th)500/ 420500/ 420500/ 420Hese length (rm)999Max Intetemperature (°C)404040Length x width x height (mm)365 x 34 5 x 90395 x 345 x 90395 x 345 x 90ModelE 145.4 9 P X.TR18.618.6ModelE 145.4 9 P X.TR128471187128471187Ref. no.128471187128471187128471187Pompersure (barl/MPA)Max 145 (max 15Max 145/ max 15.5Valage (vi)200 - 240230 - 240230 - 240Power consumption (A)999Max intet megnature (°C)404040Length x wild x height (mm)999Max intet megnature (°C)18.618.618.6Length x wild x height (mm)999Max intet megnature (°C)18.618.618.6Length x wild x height (mm)18.618.618.6Length x wild x height (mm)18.618.618.6Length x wild x height (mm)18.618.6 <td< th=""><th>Model</th><th>E 145.4-9 PAD X- TRA UK</th><th>E 145.4-9 POWER X-TRA UK</th><th>E 145.4-9 X-TRA EU</th></td<>	Model	E 145.4-9 PAD X- TRA UK	E 145.4-9 POWER X-TRA UK	E 145.4-9 X-TRA EU
Water flow Qmax/Qiec (i/h)500 420500 420500 420Hose length (m)999Max. inlet temperature (*C)404040Length x width x height (mm)355 x 345 x 900355 x 345 x 900355 x 345 x 900Weight (kg)18.618.618.618.6ModelE145.49 P.D.X.RE145.49 P.D.X.TRE145.49 P.D.X.TRRef. no.128471187128471180128471181Technical specifications128471187230 - 240230 - 240Pump pressure (bar/MPa)210 - 240230 - 240230 - 240Quage (v)200 - 240200 - 240500 420Yater flow Qmax/Qiec (i/h)999Max. inlet temperature (*C)4040Hose length (m)999Max. inlet temperature (*C)404040Length x width x height (mm)355 x 345 x 900355 x 345 x 90Weight (kg)18.618.618.618.6Model18.618.618.618.6Model18.618.618.618.6Model18.618.618.618.6Model18.618.618.618.6Model18.618.618.618.6Model18.618.618.618.6Max. inlet temperature (*C)230 - 240230 - 240Max. inlet temperature (*C)230 - 240230 - 240Max. inlet temperature (*C)230 - 240230 - 240Ma	Ref. no.	128471192	128471194	128471185
Hose length (m)999Max. inlet temperature ("C)404040Length x width x height (mn)395 x 345 x 900395 x 345 x 900395 x 345 x 900Weight (kg)16.618.618.618.6ModelElds-0 PAX TR2184 PAX TR2184 PAX TR2184 PAX TRRef. no.2887 11872184 T189220 400220 400Yotage (V)201212121Power consumption (A)9.59.59.59.5Water flow QmaxQiec (M)9.09.09.09.0Maxid th height (mn)9.59.59.59.5Weight (kg)18.618.618.618.6Model19.59.59.59.59.5Water flow QmaxQiec (M)9999Maxid th height (mn)395 x 345 x 900395 x 345 x 900395 x 345 x 900Weight (kg)18.618.618.618.6Fert. no.1245 PAY RET1245 PAY RET1245 PAY RETPower consumption (A)9999Maxid th height (mn)395 x 345 x 900395 x 345 x 900395 x 345 x 900Noted18.618.618.618.6Power consumption (A)144040Length x width x height (m2)124 PAY RET124 PAY RETPower consumption (A)1414.614.6Power consumption (A)1414.614.6Power consumption (A)1414.61	Technical specifications			
Max. inlet emperature (*C)404040Length x width x height (mm)395 x 345 x 900395 x 345 x 900395 x 345 x 900Weight (kg)18.618.618.618.6ModelE 145-4° PA X-RAE 145-4° PA X-RAE 145-4° PA X-RAE 145-4° PA X-RARef. no.128471187E 145-4° PA X-RA2128471191Technical specifications320 - 240220 - 240220 - 240Pump pressure (bar/MPa)230 - 240230 - 240230 - 240Voltage (v)2.12.12.1Power consumption (A)9.59.59.5Water flow Qmax/Qiec (I/h)500/ 420500/ 420500/ 420Hose length (m)999Max. iniet temperature (*C)404040Length x width x height (mm)395 x 345 x 900395 x 345 x 900Weight (kg)18.618.618.6Model18.618.618.6Model19128471192128471193Technical specifications12847187128471193Pump pressure (bar/MPa)395 x 345 x 900395 x 345 x 900Youtage (v)18.618.618.6Ref. no.128471193128471193Technical specifications128471193Pump pressure (bar/MPa)128471193Youtage (v)1212Youtage (v)1212Youtage (v)1212Youtage (v)1212Youtage (tow)1212Youtage (t	Water flow Qmax/Qiec (I/h)	500/ 420	500/ 420	500/ 420
Length x width x height (mm)         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6         18.6           Model         É 145.4.9 P X-TRA         É 145.4.9 P AX-TRA         É 145.4.9 P AX-TRA         E 145.4.9 P AX-TRA           Ref. no.         128471187         128471187         128471189         128471187           Technical specifications          1230 - 240         230 - 240         230 - 240           Notage (V)         230 - 240         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1         2.1           Power consumption (A)         9.5         9.5         9.5         9.5           Vater flow Qmax/Qice (I/h)         9         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6         18.6           Model         18.6         18.6         18.6         18.6           Power consumption (A)         2         2	Hose length (m)	9	9	9
Weight (kg)18.618.618.6ModelÉ 145.4.9 PAX.TRÉ 145.4.9 PAX.TRÉ 145.4.9 PAX.TRRef. no.128471187128471189128471189Technical specifications128471187Max 145/max 14.5Max 145/max 14.5Voltage (V)230 - 240230 - 240230 - 240Rated power (kW)2.12.12.1Power consumption (A)9.59.59.5Vater flow Qmax/Qice (I/h)500/ 420500/ 420500/ 420Hose length (m)999Max. inlet temperature (°C)404040Length x width x height (mm)395 x 345 spon395 x 345 sponNodelE 154.54 PAX.TR128471183128471183Pump pressure (bar/MPa)500/ 420500/ 420500 420Nodel18.618.618.6Nodel18.618.618.6Pump pressure (bar/MPa)500 420500 420520 -240Kef. no.128471183128471183128471183Pump pressure (bar/MPa)128471183128471183Pump pressure (bar/MPa)12	Max. inlet temperature (°C)	40	40	40
Model         E 145.4.9 P X:TRA         E 145	Length x width x height (mm)	395 x 345 x 900	395 x 345 x 900	395 x 345 x 900
Model         EU         EU         EU         EU         EU         TRA EU           Ref. no.         128471187         128471189         128471191         128471193         128471193           Technical specifications         Max 145/max14.5         Max 145/max14.5 <td>Weight (kg)</td> <td>18.6</td> <td>18.6</td> <td>18.6</td>	Weight (kg)	18.6	18.6	18.6
Technical specifications       Nax 145/max 14.5       Max 145/max 14.5         Pump pressure (bar/MPa)       Max 145/max 14.5       Max 145/max 14.5         Voltage (V)       230 - 240       230 - 240         Rated power (kW)       2.1       2.1       2.1         Power consumption (A)       9.5       9.5       9.5         Water flow Qmax/Ciec (I/h)       500/ 420       500/ 420       500/ 420         Hose length (m)       9       9       9         Max. inlet temperature (*C)       40       40       40         Length x width x height (mm)       395 x 345 x 900       395 x 345 x 900       395 x 345 x 900         Weight (kg)       18.6       18.6       18.6       18.6         Model       18.6       18.6       18.6       18.6         Power consumption (A)       2.0       2.0       2.0       2.0         Nodel       18.6       18.6       18.6       18.6         Pump pressure (bar/MPa)       2.1       2.0       2.0       2.0         Voltage (V)       2.0       2.0       2.0       2.0         Reide power (kW)       2.1       2.0       2.0       2.0         Voltage (V)       2.0       2.0       2	Model			
Pump pressure (bar/MPa)         Max 145/ max 14.5         Max 145/ max 14.5         Max 145/ max 14.5           Voltage (V)         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1           Power consumption (A)         9.5         9.5         9.5           Water flow Qmax/Qiec (t/h)         500/ 420         500/ 420         500/ 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Nodel         18.6         18.6         18.6         18.6           Model         18.6         18.6         128471193           Technical specifications         128471193         230 - 240           Rated power (kW)         2.1         230 - 240           Rated power (kW)         2.1         230 - 240           Rated power (kW)         2.1         2.1           Power consumption (A)         9.5         35.5           Vataer (fow Qmax/Qiec (t/h)         5.5         5.5           Vataer flow Qmax/Qiec (t/h)         9         9.5	Ref. no.	128471187	128471189	128471191
Voltage (V)         230 - 240         230 - 240         230 - 240           Rated power (kW)         2.1         2.1         2.1         2.1           Power consumption (A)         9.5         9.5         9.5           Water flow Qmax/Qiec (l/h)         500/ 420         500/ 420         500/ 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Veight (kg)         18.6         18.6         18.6         18.6           Model         E145 4-9 POWER X-TRA EU         230 - 240         230 - 240           Ref. no.         128471193         230 - 240         230 - 240           Yotage (V)          230 - 240         230 - 240           Rated power (kW)          9.5         35.5           Voltage (V)          9.5         50.7           Rated power (kW)          9.5         50.7           Power consumption (A)          9.5         50.7           Water flow Qmax/Qiec (l/h)          500/ 420         500/ 420	Technical specifications			
Rated power (kW)         2.1         2.1         2.1           Power consumption (A)         9.5         9.5         9.5           Water flow Qmax/Qiec (l/h)         500/ 420         500/ 420         500/ 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Veight (kg)         18.6         18.6         18.6           Model         E 145.4.9 POWER X-TRA EU         210         230 - 240           Ref. no.         128471193         230 - 240         230 - 240           Rated power (kW)         2.1         9.5         350 - 240           Rated power (kW)         2.1         9.5         350 - 240           Rated power (kW)         5.00 / 420         5.00 / 420           Power consumption (A)         9         5.00 / 420           Mose length (m)         9         9           Max. inlet temperature (°C)         9         9           Max. inlet temperature (°C)         40         40           Length x width x height (mm)         395 x 345 x 900	Pump pressure (bar/MPa)	Max 145/ max 14.5	Max 145/ max 14.5	Max 145/ max 14.5
Power consumption (A)         9.5         9.5         9.5           Water flow Qmax/Qiec (I/h)         500/ 420         500/ 420         500/ 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6           Model         £ 145.4-9 POWER X-TRA EUP         128471193           Fecf. no.         128471193         128471193           Technical specifications         1230 - 240         230 - 240           Rated power (kW)         9.5         350/ 420           Power consumption (A)         9.5         500/ 420           Hose length (m)         9         9           Max. inlet temperature (°C)         40         9           Max. inlet temperature (°C)         40         40	Voltage (V)	230 - 240	230 - 240	230 - 240
Water flow Qmax/Qiec (l/h)         500/ 420         500/ 420         500/ 420           Hose length (m)         9         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6         18.6           Model         E 145 4-9 POWER X-TRA EU         X-TRA EU         128471193           Fech no.         128471193         128471193           Pump pressure (bar/MPa)         Max 145/ max 14.5         230 - 240           Voltage (V)         230 - 240         230 - 240           Rated power (kW)         9         9           Power consumption (A)         9.5         500/ 420           Hose length (m)         9         9           Max. inlet temperature (°C)         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900	Rated power (kW)	2.1	2.1	2.1
Hose length (m)         9         9           Max. inlet temperature (°C)         40         40         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6         18.6           Model         E 145 4.9 POWER X-TRA EU         X-TRA EU         128471193           Ref. no.         I 28471193         128471193           Technical specifications         Max 145/ max 14.5         230 - 240           Notage (V)         I 230 - 240         230 - 240           Rated power (kW)         1.1         9.5           Vater flow Qmax/Qiec (l/h)         I 500/ 420         9.5           Hose length (m)         9         40           Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900	Power consumption (A)	9.5	9.5	9.5
Max. inlet temperature (°C)404040Length x width x height (mm)395 x 345 x 900395 x 345 x 900395 x 345 x 900Weight (kg)18.618.618.618.6Model18.618.618.618.6Model128471193128471193Fer. no.128471193128471193Pump pressure (bar/MPa)305 x 345 x 900Votage (V)230 - 240230 - 240Rated power (kW)9.5500 / 420Power consumption (A)9500 / 420Hose length (m)940Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Water flow Qmax/Qiec (I/h)	500/ 420	500/ 420	500/ 420
Length x width x height (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         18.6         18.6         18.6         18.6           Model         E 145.4-9 POWER X-TRA EU         E 145.4-9 POWER X-TRA EU         128471193           Ref. no.         128471193         128471193           Technical specifications         Max 145/ max 14.5         230 - 240           Rated power (kW)         2.1         230 - 240           Power consumption (A)         9.5         3500/ 420           Hose length (m)         9         305 x 345 x 900           Max. inlet temperature (°C)         40         305 x 345 x 900	Hose length (m)	9	9	9
Weight (kg)18.618.618.6ModelE 145.4-9 POWER X-TRA EURef. no.128471193Technical specifications128471193Pump pressure (bar/MPa)Max 145/ max 14.5Voltage (V)230 - 240Rated power (kW)2.1Power consumption (A)9.5Vater flow Qmax/Qiec (I/h)500/ 420Hose length (m)9Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Max. inlet temperature (°C)	40	40	40
ModelÉ 145.4-9 POWER KTRA EURef. no.128471193Technical specificationsMax 145/ max 14.5Pump pressure (bar/MPa)Max 145/ max 14.5Voltage (V)230 - 240Rated power (kW)2.1Power consumption (A)9.5Water flow Qmax/Qiec (I/h)500/ 420Hose length (m)9Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Length x width x height (mm)	395 x 345 x 900	395 x 345 x 900	395 x 345 x 900
ModelX-TRA EURef. no.128471193Technical specifications128471193Pump pressure (bar/MPa)Max 145/ max 14.5Voltage (V)230 - 240Rated power (kW)2.1Power consumption (A)9.5Water flow Qmax/Qiec (I/h)500/ 420Hose length (m)9Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Weight (kg)	18.6	18.6	18.6
Technical specifications       Max 145/ max 14.5         Pump pressure (bar/MPa)       Max 145/ max 14.5         Voltage (V)       230 - 240         Rated power (kW)       2.1         Power consumption (A)       9.5         Water flow Qmax/Qiec (l/h)       500/ 420         Hose length (m)       9         Max. inlet temperature (°C)       40         Length x width x height (mm)       395 x 345 x 900	Model			
Pump pressure (bar/MPa)Max 145/ max 14.5Voltage (V)230 - 240Rated power (kW)2.1Power consumption (A)9.5Water flow Qmax/Qiec (I/h)500/ 420Hose length (m)9Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Ref. no.			128471193
Voltage (V)230 - 240Rated power (kW)2.1Power consumption (A)9.5Water flow Qmax/Qiec (I/h)500/ 420Hose length (m)9Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Technical specifications			
Rated power (kW)2.1Power consumption (A)9.5Water flow Qmax/Qiec (l/h)500/ 420Hose length (m)9Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Pump pressure (bar/MPa)			Max 145/ max 14.5
Power consumption (A)9.5Water flow Qmax/Qiec (I/h)500/ 420Hose length (m)9Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Voltage (V)			230 - 240
Water flow Qmax/Qiec (I/h)500/ 420Hose length (m)9Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Rated power (kW)			2.1
Hose length (m)9Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Power consumption (A)			9.5
Max. inlet temperature (°C)40Length x width x height (mm)395 x 345 x 900	Water flow Qmax/Qiec (I/h)			500/ 420
Length x width x height (mm) 395 x 345 x 900	Hose length (m)			9
	Max. inlet temperature (°C)			40
Weight (kg) 18.6	Length x width x height (mm)			395 x 345 x 900
	Weight (kg)			18.6



ullet Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

	Accessories	Ref. no.	Min. required	E 145.4-9 X- TRA UK	E 145.4-9 P X-TRA UK	E 145.4-9 PA X-TRA UK
Brush						
	AUTOBRUSH ALONE	6411131	0	0	0	0
•	Car brush head	128500463	0	0	0	o
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0	0	o
6	Garden brush head	128470457	0	0	0	o
	RIM BRUSH HEAD	128470458	0	0	0	o
	ROTARY BRUSH	126411395	0	0	0	•
-	ROTARY BRUSH	6410762	0	0	o	o
Accessory						
T	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0	0	0	o
0	DRAIN AND TUBE CLEANER ALTO	6410766	0	0	o	o
	G4 NOZZLE TUBE SHORT	128500676	0	•	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•	•	•



	Accessories	Ref. no.	Min. required	E 145.4-9 X- TRA UK	E 145.4-9 P X-TRA UK	E 145.4-9 PA X-TRA UK
Ç	INLET SUCTION HOSE 3M	128500673	0	0	0	0
	MULTI BRUSH	128470456	0	0	0	0
-	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0	0
	NILFISK PATIO ACCESSORY	128500702	0	0	•	•
19	NILFISK POWER PATIO	128500955	0	0	0	0
	NILFISK WATER FILTER	128500674	0	0	0	0
1 IL	ROOF CLEANER	128470040	0	0	0	0
	UNDERCHASSIS SPRAY LANCE	6410763	0	0	0	0
Ý	VSB SET - GREEN	6410891	0	0	0	0
4	WALL HOOK	106411386	0	0	0	0
-0	WATER SUCTION KIT	126411387	0	0	0	0
Accessory Kit						
<b>.</b>	MULTI BRUSH KIT	128470459	0	0	0	0



	Accessories	Ref. no.	Min. required	E 145.4-9 X- TRA UK	E 145.4-9 P X-TRA UK	E 145.4-9 PA X-TRA UK
0000	O-RING KIT CONSUMER HPW	128500292	0	0	0	0
Nozzle - High	Pressure Washer					
<i>ø</i>	C&C CAR NOZZLE	6411136	0	0	0	0
	C&C POWER SPEED	128501153	0	٠	•	•
	TORNADO CC 4 DOTS DARK BLUE	128500854	0	•	•	•
-	UNDER CARRIAGE SPRAY NOZZLE	6411135	0	0	0	0
Hose and Cor	inection					
9	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•	•	•
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0	0

• Standard equipment, <sup>O</sup> Supplementary accessories, <sup>D</sup> Mountable equipment

Accessories		Ref. no.	Min. required	E 145.4-9 PAD X-TRA UK	E 145.4-9 POWER X- TRA UK	E 145.4-9 X- TRA EU
Brush						
	AUTOBRUSH ALONE	6411131	0	0	0	0
٢	Car brush head	128500463	0	0	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0	0	0



	Accessories	Ref. no.	Min. required	E 145.4-9 PAD X-TRA UK	E 145.4-9 POWER X- TRA UK	E 145.4-9 X- TRA EU
•	Garden brush head	128470457	0	0	0	0
	RIM BRUSH HEAD	128470458	0	0	0	0
	ROTARY BRUSH	126411395	0	•	0	0
	ROTARY BRUSH	6410762	0	0	0	0
Accessory						
7	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0	0	0	0
$\bigcirc$	DRAIN AND TUBE CLEANER ALTO	6410766	0	•	0	0
	G4 NOZZLE TUBE SHORT	128500676	0	•	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•	•	•
Ç	INLET SUCTION HOSE 3M	128500673	0	0	0	0
	MULTI BRUSH	128470456	0	0	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0	0



	Accessories	Ref. no.	Min. required	E 145.4-9 PAD X-TRA UK	E 145.4-9 POWER X- TRA UK	E 145.4-9 X- TRA EU
2	NILFISK PATIO ACCESSORY	128500702	0	•	0	0
19	NILFISK POWER PATIO	128500955	0	0	•	0
	NILFISK WATER FILTER	128500674	0	0	0	0
A	ROOF CLEANER	128470040	0	0	0	0
	UNDERCHASSIS SPRAY LANCE	6410763	0	0	0	0
Ý	VSB SET - GREEN	6410891	0	0	0	0
	WALL HOOK	106411386	0	0	0	0
6	WATER SUCTION KIT	126411387	0	0	0	0
Accessory Kit	t					
	MULTI BRUSH KIT	128470459	0	0	0	0
00 <b>0</b> 0	O-RING KIT CONSUMER HPW	128500292	0	0	0	0
Nozzle - High	Nozzle - High Pressure Washer					
<i>(</i>	C&C CAR NOZZLE	6411136	0	0	0	0



	Accessories	Ref. no.	Min. required	E 145.4-9 PAD X-TRA UK	E 145.4-9 POWER X- TRA UK	E 145.4-9 X- TRA EU
	C&C POWER SPEED	128501153	0	٠	•	•
	TORNADO CC 4 DOTS DARK BLUE	128500854	0	•	•	•
<b>-?</b>	UNDER CARRIAGE SPRAY NOZZLE	6411135	0	0	0	0
Hose and Co	nnection					
9	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•	•	•
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0	0

ullet Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

	Accessories	Ref. no.	Min. required	E 145.4-9 P X- TRA EU	E 145.4-9 PA X-TRA EU	E 145.4-9 PAD X-TRA EU
Brush						
	AUTOBRUSH ALONE	6411131	0	0	0	0
•	Car brush head	128500463	0	0	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0	0	0
8	Garden brush head	128470457	0	0	0	0
	RIM BRUSH HEAD	128470458	0	0	0	0
	ROTARY BRUSH	126411395	0	0	•	•



	Accessories	Ref. no.	Min. required	E 145.4-9 P X- TRA EU	E 145.4-9 PA X-TRA EU	E 145.4-9 PAD X-TRA EU
	ROTARY BRUSH	6410762	0	0	0	0
Accessory						
	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0	0	0	•
$\bigcirc$	DRAIN AND TUBE CLEANER ALTO	6410766	0	0	0	0
	G4 NOZZLE TUBE SHORT	128500676	0	•	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•	•	•
	INLET SUCTION HOSE 3M	128500673	0	0	0	0
	MULTI BRUSH	128470456	0	0	O	O
<b>-</b>	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0	0
6	NILFISK PATIO ACCESSORY	128500702	0	•	•	•
19	NILFISK POWER PATIO	128500955	0	0	0	0
	NILFISK WATER FILTER	128500674	0	0	0	0



	Accessories	Ref. no.	Min. required	E 145.4-9 P X- TRA EU	E 145.4-9 PA X-TRA EU	E 145.4-9 PAD X-TRA EU
i u	ROOF CLEANER	128470040	0	0	0	0
	UNDERCHASSIS SPRAY LANCE	6410763	0	0	0	0
Ý	VSB SET - GREEN	6410891	0	0	0	0
	WALL HOOK	106411386	0	0	0	0
6	WATER SUCTION KIT	126411387	0	0	0	0
Accessory Kit			1			
<b>.</b>	MULTI BRUSH KIT	128470459	0	0	0	0
0000	O-RING KIT CONSUMER HPW	128500292	0	0	0	0
Nozzle - High F	Pressure Washer					
<i>•</i>	C&C CAR NOZZLE	6411136	0	0	0	0
	C&C POWER SPEED	128501153	0	•	•	•
	TORNADO CC 4 DOTS DARK BLUE	128500854	0	•	•	•
-7	UNDER CARRIAGE SPRAY NOZZLE	6411135	0	0	0	0
Hose and Con	nection					
P	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•	•	•



Accessories		Ref. no.	Min. required	E 145.4-9 P X- TRA EU	E 145.4-9 PA X-TRA EU	E 145.4-9 PAD X-TRA EU
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0	0

#### ullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	E 145.4-9 POWER X- TRA EU
Brush				
	AUTOBRUSH ALONE	6411131	0	0
1	Car brush head	128500463	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0
•	Garden brush head	128470457	0	0
	RIM BRUSH HEAD	128470458	0	0
	ROTARY BRUSH	126411395	0	0
	ROTARY BRUSH	6410762	0	0
Accessory				
7	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•
9	DRAIN AND TUBE 8M	128500461	0	0



		uent or larger cleaning tasks
IOW-DOISE DIAD-DRESIIR	washer ineal for fredi	lent or larger cleaning tasks

	Accessories	Ref. no.	Min. required	E 145.4-9 POWER X- TRA EU
$\bigcirc$	DRAIN AND TUBE CLEANER ALTO	6410766	0	0
	G4 NOZZLE TUBE SHORT	128500676	0	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•
Ç	INLET SUCTION HOSE 3M	128500673	0	0
	MULTI BRUSH	128470456	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0
2	NILFISK PATIO ACCESSORY	128500702	0	0
19	NILFISK POWER PATIO	128500955	0	•
	NILFISK WATER FILTER	128500674	0	0
à	ROOF CLEANER	128470040	0	0
	UNDERCHASSIS SPRAY LANCE	6410763	0	0
Ý	VSB SET - GREEN	6410891	0	0



The manual full laws life	I a		t or larger cleaning tasks
I ne powertui iona-lite	low-noise nign-pressure	washer ideal for frequen	t or larger cleaning tasks
rite performan, tering me,	now molect light proceeded	Machel: lacal let hequel	corranger eleanning taente

Accessories		Ref. no.	Min. required	E 145.4-9 POWER X- TRA EU
	WALL HOOK	106411386	0	0
0	WATER SUCTION KIT	126411387	0	0
Accessory Kit				
<b>.</b>	MULTI BRUSH KIT	128470459	0	0
0000	O-RING KIT CONSUMER HPW	128500292	0	0
Nozzle - High Pressure Washer				
ø	C&C CAR NOZZLE	6411136	0	0
	C&C POWER SPEED	128501153	0	•
	TORNADO CC 4 DOTS DARK BLUE	128500854	0	•
-7	UNDER CARRIAGE SPRAY NOZZLE	6411135	0	0
Hose and Connection				
9	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0

