



FCS-3073 Version: 1

1 Power supply unit is to be ordered separately.

GEMINI Fixed Dome IP Network Camera, 2-Megapixel, 802.3af PoE, Vandalproof, Indoor/Outdoor

The LevelOne FCS-3073 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP66 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3073 offers 2-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Key Features

- Weatherproof IP66-rated housing
- 2-Megapixel (1920 x 1080) high-definition resolution
- Video compression: H.264, MJPEG
- IEEE 802.3af PoE compliant to simplify deployment and installation
- Removable IR-cut filter for day and night surveillance
- Supports IPv4/IPv6 network operation
- Vandal-proof IK10-rated housing

- Built-in Micro SD/SDHC card slot for local storage

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS

Image Sensor:

2-Megapixel 1/2.8" ProgressiveScan CMOS

Lens:

Board lens, Fixed-focal, f=6.0mm, F2.0

www.level1.com Page 1 of 4

Port:

1 x RJ-45 10/100 Mbps PoE port

1 x MicroSDHC card slot

Button/Knob:

Reset Button

Shutter Time:

 $1 \sim 1/10,000$ sec.

Angle of View:

52°

Pan/Tilt/Zoom:

digital zoom

Video Compression:

H.264 / MJPEG

Resolution:

2M (1920x1080)

Output Video Format:

AVI

Power Input:

802.3af PoE

Power Consumption:

3.5W

Data Rate:

10/100Mbps

Storage Capacity:

SD/MicroSD memory card of up to 16GB

Features

General:

Backup: MicroSDHC card slot for local storage

IPv6: IPv4/IPv6 network operation

Security:

Alarm and Notification: Alarm: Motion Detection; Tampering Detection; Network Failure Detection

Notification: HTTP, FTP, SMTP

Access Control: Multi-level user access with password protection

IP address filtering

IEEE 802.1X network access control HTTPS encrypted data transmission

Video:

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure
- AGC/AWB/AES
- Back Light Compensation (BLC)
- Wide Dynamic Range (WDR)
- 3D Noise Reduction (3DNR)
- Flip & Mirror
- Portrait Mode
- Privacy Mask
- Time Stamp and Text Caption Overlay

Image Layout:

Streaming: Up to 2 video streams

Motion Detection

www.level1.com Page 2 of 4

Performance

Number of Clients:

20

Frame Rate (fps):

30 fps at 1920x1080; 30 fps at 1280x1024

Minimum illumination:

Color: 0.01Lux @(F1.2,AGC ON), 0.028Lux @(F2.0,AGC ON) B/W: 0.001Lux @(F1.2,AGC ON), 0.0028Lux @(F2.0,AGC ON)

Environment

Operating Temperature (°C):

Operating: -30 °C - 60 °C

Operating Humidity (Non-condensing):

Operating: 10% ~ 90%

Installation:

Ceiling Mount with vandal resistant IK10-rated

Physical Specifications

Dimensions (W x D x H mm):

 $99.9 \times 97.5 \times 46.5 \text{ mm}$

Weight (g):

400 g

Approval and Compliance

EMI/EMS:

CE, RoHS, FCC, ONVIF

Environmental Test:

Weather proof IP66-rated housing

Vandal Resistant IK10-reted

Others

Supported Browsers:

Internet Explorer 6 or above

Order Information

FCS-3073

Package Contents

FCS-3073

Screw Kit

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Optional Accessory



CAS-7303

Pole Mount Bracket, Clamping Range 2.6"-5"

www.level1.com Page 3 of 4



CAS-7307

Corner Mount Bracket



CAS-7321

In-ceiling Mount Bracket



CAS-7322

Wall Mount Bracket



CAS-7323

Wall Mount Bracket with Junction Box



CAS-7324

Pendant Mount Bracket

www.level1.com Page 4 of 4