

Rack UPS, 1000 VA, black EG-UPSRACK-10

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Features

- Automatic output voltage regulation (AVR)
- Rack 3.4U metal case
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

Q'ty in crtn, pcs	1
Crtn volume, CUM	0.04464
Crtn weight, kgs	17.34
Individual package size LxWxH:	525x400x225 mm
Carton size LxWxH:	620x450x160 mm
Country of origin	CN
Barcode	8716309124775
Customs code	8504408590

Package contents

- UPS
- Power cord
- USB cable
- Software CD
- Spare fuse

Specifications

UPS type: line interactive, pure sine wave
 Input: 220V AC \pm 25%, 50Hz / 60Hz \pm 10%
 Output: 220V AC \pm 10%, 50Hz / 60Hz \pm 0.5% (on battery)
 Output power factor: 0.8
 Inverter output efficiency (resistive load): 85%, any load type is allowed
 Switching time: no more than 10 ms (typically 6 ms)
 Backup time: 8...20 mins (depends on the load)
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 7 Ah / 2.0 kg x 2 pcs
 Charge time: up to 90% after 6-8 hours
 Sockets: input IEC C14, outputs: Schuko EU type x 1 pc, IEC C13 x 3 pcs

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Certificates

