

# Delock USB Condenser Microphone Set - for Podcasting, Gaming and Vocals

## Description

This USB condenser microphone by Delock can be used for high-quality voice and vocal recordings.

### Optimal recordings

The microphone has a cardioid polar pattern (unidirectional) and captures the sound ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

### Dual Layer Pop Filter & Windscreen

Due to the included dual layer pop filter and the windscreen, the recording quality is further optimized. Annoying wind noises are optimally filtered.

### Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.

### Stable & non-slip stand

The metal base with rubber feet ensures that the microphone stands stable on the table. The shock mount (spider) ensures vibration-free recording. The table stand can be folded and transported easily if required.



## Specification

- Connector: 1 x USB 2.0 Type-A male
- Directivity: unidirectional
- Sensitivity: -47 dB +/- 3 dB
- Frequency range: 20 Hz - 20 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 60 dB
- Impedance: 2.2 kOhm
- Cable length: ca. 1.5 m
- Colour: black
- Dimensions (LxWxH): ca. 150 x 45 x 35 mm
- USB bus powered
- Plug & Play

## System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- USB microphone
- Table stand
- Shock mount (spider)
- Pop filter
- Windscreen
- User manual

Item no. 66331

EAN: 4043619663316

Country of origin: China

Package: • Retail Box



Images



**General**

Function:	Plug & Play
Supported operating system:	Chrome OS Mac OS 10.9 or above Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above

**Interface**

connector:	1 x USB 2.0 Type-A male
------------	-------------------------

**Technical characteristics**

Frequency range:	20 Hz - 20 kHz
Voltage:	USB bus powered
Sensibility:	- 47 dB +/- 3 dB
Sample rate:	16 Bit / 44.1 kHz
Signal noise ratio (SNR):	ca. $\geq$ 60dB
Directivity:	uni-directional

**Physical characteristics**

Cable length:	1.5 m
Length:	150 mm
Width:	45 mm
Height:	35 mm
Colour:	black