



FCS-3085 Version: 1

! Power supply unit is to be ordered separately.

GEMINI Varifocal Dome IP Network Camera, 4-Megapixel, Indoor/Outdoor, 802.3af PoE, IR LEDs, two-way audio

The LevelOne FCS-3085 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP66 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3085 offers 4-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Key Features

- 4-Megapixel high-definition resolution
- 2.8-12 mm adjustable Vari-focal length for wide angle surveillance
- Power support: PoE (IEEE 802.3af)
- Video compression: H.264, MJPEG
- Vandal-proof IK10-rated housing
- Built-in infrared LEDs for night viewing up to 30m
- Built-in Micro SDHC/SDXC card slot for local storage
- Weatherproof IP66-rated housing
- Supports motion detection (Intrusion/camera tampering/line crossing) and event notification
- Free surveillance and CMS (Central Management System) software packages with 64-channel license

Specifications

System Specifications

Standards & Protocols:

TCP/IP (IPv4), UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour, IEEE802.1x

Image Sensor:

1/3" Progressive Scan CMOS

Lens:

2.8 - 12 mm @ F1.4, Vari-focal, Auto Iris

Port:

10/100Mbps (100Base-T) RJ45 Ethernet interface

Power Connector

Audio: In/Out

I/O terminal block (1 DI/1 DO)

1 x MicroSDHC/ MicroSDXC card slot

**Button/Knob:**

Reset Button

Indicator:

Power

IR Cut Filter:

IR cut filter with auto switch

IR LED:

Up to 30m

Shutter Time:

1/3 s ~ 1/100,000 s

Angle of View:

112°~33.8°

Video Compression:

H.264/MJPEG

Resolution:

50Hz: 20fps (2688×1520), 25fps(1920×1080), 25fps(1280×720)

60Hz: 20fps (2688×1520), 30fps (1920×1080), 30fps(1280×720)

Output Video Format:

RAW

Audio Compression:

G.711/G.722.1/G.726/MP2L2, 64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2)

Power Input:

12V DC±10%, PoE (802.3af)

Power Consumption:

Max. 5.5 W

Data Rate:

32Kbps~16Mbps

Storage Capacity:

Support Micro SD/SDHC/SDXC card with ANR (up to 128G)

Features

General:

Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser, Dual Stream Server.

PoE:

PoE(802.3af, class 3)

Security:

One-key reset, Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering, Anonymous access

Video:

- Adjustable image size, quality and bit rate
- Configurable brightness, sharpness, contrast, saturation, white balance and exposure
- AGC/AWB/AES
- Back Light Compensation (BLC)
- Wide Dynamic Range (WDR) 120dB
- 3D Noise Reduction (3DNR)
- Flip & Mirror
- Rotate Mode
- Portrait Mode
- Privacy Mask
- Automatic Day/Night
- ICR

Audio:
G.711/G.722.1/G.726/MP2L2

Performance

Number of Clients:

10

Frame Rate (fps):

50Hz: 20fps , 25fps, 25fps

60Hz: 20fps , 30fps ,30fps

Minimum illumination:

0.01Lux @(F1.2,AGC ON), 0.014 Lux @(F1.4,AGC ON), 0 Lux with IR

Environment

Operating Temperature (°C):

-30 °C ~ 60 °C (-22 °F ~ 140 °F)

Operating Humidity (Non-condensing):

Humidity 95% or less (non-condensing)

Physical Specifications

Dimensions (W x D x H mm):

140

Weight (g):

140

Color:

99

Approval and Compliance

EMI/EMS:

CE,FCC,UL

Safety:

IK10

Environmental Test:

IEC60068-2-75Eh, EN50102,

Others:

ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI,ISO-9001 certified factory

RoHS

Others

Supported Browsers:

Microsoft Windows 10/8/7/Vista/XP Internet Explorer

Order Information

FCS-3085

Package Contents

FCS-3085

Screw Kit

Resource CD (User Manual, Utility, QIG)



Optional Accessory



CAS-7303

Pole Mount Bracket, Clamping Range 2.6"-5"




CAS-7307

Corner Mount Bracket



CAS-7309

Weather Shield



CAS-7313

In-ceiling Mount Bracket



CAS-7314

Wall Mount Bracket



CAS-7315

Wall Mount Bracket, Aluminum Alloy



CAS-7316

Wall Mount Bracket with Junction Box, Aluminum Alloy



CAS-7317


Pendant Mount Bracket



CAS-7318
Weather Shield



CAS-7319
Junction Box



CAS-7320
In-ceiling Mount Bracket

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.